

HGM Series


Natural Gas Heater Module

This state-of-the-art natural gas heater module is the simplest way to add heat to your existing cold water pressure washers.

Natural gas or LP-gas fired natural draft with asprating-type burner, 10 inch stack




Electronic ignition with pilot



On/off burner switch



Fork truck accessible



Draft diverter included



Natural Gas Installations Recommendation:
Mi-T-M's natural gas heater module must have a clearance of 2 feet on both sides and at the front of the unit



HGM-3506-0E10 shown with JP-2703-0MHB

Additional Features

- Incoming power 120 volt or 240 volt, single phase
- Pressure relief valve
- Adjustable thermostat
- 24 volt control system
- 1/2 inch schedule 80 vertical coil assembly with 7 pancake
- Quality gas valve with regulator (max. input 1/2 PSI)
- Inlet and outlet quick connects
- Powder coated frame assembly
- 3/8 inch x 12 foot jumper hose with quick connects included (to hook up to existing pressure washer)

Lorchem Technologies, Inc.

1150 Davis Road, Suite J

Elgin, IL 60123

Ph. 847/468-8800

Fax. 847/468-8811

Model #	HGM-3506-0E10
Max. PSI	3500
Max. GPM	6.0
Nat. Gas BTU	338,000 per hr.
LP-Gas BTU	326,000 per hr.
Dim. (LxWxH)	24.25in.x26.25in.x49.75in.
Shipping weight	466 lbs.
Net weight	346 lbs.

Options:

HX-0105

Liquid propane - Converts natural gas heater module to operate on liquid propane (vapor only)

HX-0129

460V, 3 phase incoming power option - For when you have 460 volts of power available

Gas Supply Line

Natural Gas

7-8" water column input

LP-Gas

12-14" water column input

Recommended Pipe Sizes for Gas Supply Line

Natural Gas

LP-Gas

Distance to Unit from Regulator	Pipe Size	Distance to Unit from Regulator	Pipe Size
0-50 feet	1½" 1PS	0-50 feet	1" 1PS
50-100 feet	2" 1PS	50-100 feet	1½" 1PS
100-200 feet	2½" 1PS	100-200 feet	1¾" 1PS

Model #	HX-0105	HX-0129
HGM-3506-0E10	●	●