

CLASSIC SERIES

HOT WATER ► GASOLINE POWERED ► SKID

- **Variable PSI and Temperature**
- **Reliable Belt-Drive Kärcher Crankcase Pumps**
- **Compact, High-Efficiency Burner**
- **Low-Fuel Shut-Off**

Heavy-gauge 1/4" steel frame with powder coat finish for all-weather protection; with vibration isolators and forklift guides

Infinitely variable operating pressure, water volume, temperature control, and detergent metering

Reliable gasoline-powered Honda or Vanguard engines, all with electric start

Industrial-duty, tri-plunger, oil-bath, belt-drive Kärcher KT pump with 5-year warranty and Tru-Trak belt adjustments; has brass pump head and operates at a low RPM for a trouble-free operating life



Insulated Kärcher pivoting spray wand with a unique 25° Power Nozzle that delivers 40% more cleaning power due to even-impact spray pattern

Rust-free 11 gal. polyethylene diesel and gasoline tanks provide hours of uninterrupted operation

Tri-lingual operating instructions for owner liability protection

ETL certified to the rigid UL-1776 and CSA 22.2 safety standards

Float Tank, with built-in anti-scale system prevents down time caused by mineral deposits; water inlet filter prevents contaminated water from damaging the pump

Safety relief valve protects pump from overheating and prevents excessive pressure build up

Easy-to-use controls, plus warning lights that monitor fuel and scale inhibitor levels and low-fuel shut-off to protect fuel pump

Unsurpassed Kärcher safety features include pressure switches, rupture disk, pulsation dampener, and low water cut-off that shuts down burner when incoming water volume is insufficient or interrupted

Built-in variable steam valve creates steam spray of up to 285°F

Detergent metering valve allows for infinitely variable application of soap while washing in high-pressure mode

50' Kärcher long-life hose rated for beyond 300°F and 5800 PSI



Ergonomically designed soft-grip Easy Press shutoff gun minimizes operator fatigue

DISTRIBUTED BY:
Lorchem Technologies, Inc.

 1150 Davis Rd., Ste. J
 Elgin, IL 60123

P: 847-468-8800 F: 847-468-8811

1-800-788-8867

www.lorchem.com

Model	Order No.	GPM	PSI	Engine	HP	Start	Pump	Ship Wt
HDS 4.0/32 Pe Cage	1.575-615.0	3.0 - 4.0	870 - 3200	Honda	13	Electric	Kärcher KT	580 lbs
HDS 5.0/32 Pe Cage	1.575-616.0	3.0 - 5.0	870 - 3200	Vanguard	16	Electric	Kärcher KT	600 lbs
HDS 5.5/35 Pe Cage	1.575-617.0	3.0 - 5.5	870 - 3500	Honda	20	Electric	Kärcher KT	650 lbs

Dimensions: 51"L x 33"W x 43"H