KÄRCHER

makes a difference

PRESSURE WASHERS

Lorchem Technologies, Inc.
1150 Davis Road, Suite J • Elgin, IL 60123
(800) 788-8867 • info@lorchem.com • www.lorchem.com
We Know How To Get Things CLEAN

Professional | 2018

HDS UPRIGHT CLASS

Mobility at its finest.

This high-performance, robust upright machine offers outstanding maneuverability, easy transport and intuitive operation. Ideal for tradesmen, commercial use and contract cleaners.

Innovative design

- Effortless transport over landings or stairs and space saving storage
- Large, flat-free tires for unpaved surfaces
- Large fine mesh filter reliably protects against dirt particle damage.

EASY!Force Trigger Gun

- EASY!Force gun with cruise control like technology - uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use.

Technical data

Model	Part No.	GPM	PSI	Drive	HP	Electrical	Amps	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HDS 1.7/12 U Ed	1.064-907.0	1.7	1200	Direct	2.3	110-120V / 1ph	12.5	Kärcher Axial	178	28 x 28 x 46

Accessories

	Order No.	Description
■	4.118-005.0 ■	EASY!Force trigger gun (German model) - zero force required.
■	4.112-006.0 ■	33" spray lance
■	6.110-034.0 ■	33' high-pressure hose
■	4.117-027.0 ■	Triple jet nozzle, 032
□	2.112-015.0 ■	Gutter cleaning lance
□	4.112-032.0 ■	Underbody lance
□	6.110-051.0 ■	High-pressure hose, 10m DN8, suitable for food industry, extension piece
□	6.110-049.0 ■	Pipe cleaning hose
□	2.111-013.0 ■	FR 30 ME surface cleaner
□	2.111-011.0 ■	Surface cleaner FR 30
□	4.115-000.0 ■	Wet blasting attachment
□	4.113-003.0 ■	Rotating washing brush natural fiber bristles
□	4.113-004.0 ■	Rotating washing brush nylon bristles
□	2.113-000.0 ■	Power nozzle 25° spray angle
□	4.114-019.0 ■	Dirtblaster Nozzle 035
□	4.637-033.0 ■	Detergent injector for high pressure
□	2.115-000.0 ■	Quick coupling
□	2.115-001.0 ■	Plug nipple
□	4.112-000.0 ■	41" Spray lance

■ Included □ Optional

■ Compatible with EASY!Lock

HDS COMPACT CLASS

It's all in the detail.

Kärcher's German-built electric hot water machines are the most advanced on the market, featuring Kärcher's patented axial pump integrated with a 2-pole motor for optimum efficiency. Kärcher's efficient and compact downdraft-fired burner uses far less fuel than standard heat exchangers. Units come standard with low-fuel shut-off, low-water protection, high-temperature shut-off, thermal overload protection, soft-grip gun, and 50' hose. All units are ETL certified to UL and CSA standards.

Efficiency

- eco!efficiency mode – economical and environmentally friendly, even during longer periods of use.
- Reduces fuel consumption and CO^2 emissions by 20%.

Mobility

- Robust wheels and steering mechanism for maneuverability.
- Large integrated handles in the chassis.
- Integrated tilting aid for effortlessly negotiating obstacles such as steps and curbs.

Technical data

Model	Part No.	GPM	PSI	Drive	HP	Electrical	Amps	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HDS 2.3/12 C Ed	1.272-901.0	2.3	1100	Direct	2.8	110-120V/1ph	18.5	Kärcher Axial	270	40 x 28 x 41
HDS 3.0/20 C Ea	1.170-903.0	1.3-2.9	460-2000	Direct	5.6	220-240V/1ph	18.5	Kärcher Axial	285	40 x 28 x 41

Accessories

	Order No.	Description
■	4.118-005.0 ■	EASY!Force trigger gun (German model) - zero force required.
■	4.112-000.0 ■	41" spray lance
■	6.110-030.0 ■	High pressure hose, 15m (50'), both sides EASY!Lock, ID 8
■	4.117-037.0 ■	Triple jet nozzle, 050 (for machine 1.272-901.0)
■	2.113-007.0 ■	Power nozzle, 042 (for machine 1.170-903.0)
□	4.111-041.0 ■	Adapter for EASY!Force trigger gun connection to 3/8" hose

■ Included □ Optional

■ Compatible with EASY!Lock

HDS MID CLASS

Jack of all trades.

The perfect hot water pressure washer for car dealers, building service contractors, agriculture and municipal use. The mid class machines set the standard in performance, ease of use, economy and service life.

ETL LISTED · 7 YEAR PUMP WARRANTY · EASY!Force · 1 x 360° EASY!Lock · FLAT FREE TIRES · Biodiesel

eco!efficiency

Efficiency

- eco!efficiency mode – economical and environmentally friendly, even during longer periods of use.
- Reduces fuel consumption and CO^2 emissions by 20%.

EASY!Force Trigger Gun

- EASY!Force gun with cruise control like technology - uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use.

Technical data

Model	Part No.	GPM	PSI	Drive	HP	Electrical	Amps	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HDS 4.0/20-4M Ea	1.071-907.0	2.0-4.0	460-2000	Direct	8	220-240V / 1ph	28	Kärcher Axial	495	51 x 32 x 45
HDS 4.5/22-4M Ea	1.071-908.0	2.4-4.5	460-2250	Direct	9.5	220-240V / 1ph	30	Kärcher Axial	501	51 x 32 x 45
HDS 3.5/30-4M Ea	1.071-911.0	2.0-3.5	460-3000	Direct	9.5	220-240V / 1ph	30	Kärcher Axial	500	51 x 32 x 45
HDS 3.5/23-4M Eg	1.071-906.0	2.0-3.5	460-2300	Direct	8.1	200-208V / 1ph	30	Kärcher Axial	500	51 x 32 x 45

Accessories

	Order No.	Description
■	4.118-005.0 ■	EASY!Force trigger gun (German model) - zero force required.
■	4.112-000.0 ■	41" spray lance
■	6.110-029.0 ■	50' EASY!Lock Longlife hose with ANTI!Twist connection
■	2.113-010.0 ■	Power nozzle, 048 (for machine 1.071-906.0)
■	2.113-012.0 ■	Power nozzle, 062 (for machine 1.071-908.0)
■	2.113-021.0 ■	Power nozzle, 040 (for machine 1.071-911.0)
■	2.113-026.0 ■	Power nozzle, 060 (for machine 1.071-907.0)
☐	4.111-041.0 ■	Adapter for EASY!Force trigger gun connecting to 3/8" hose
☐	8.918-280.0	Hose, 3/8" x 6'
☐	4.118-008.0 ■	Servo control

■ Included ☐ Optional

■ Compatible with EASY!Lock

For more information, contact Lorchem Technologies at:
(800) 788-8867 · info@lorchem.com · www.lorchem.com

HDS SUPER CLASS

Full-size power.

Super class hot water pressure washers offer optimum cleaning performance, easy handling and the latest technology.

Service switch

- Service switch offers a choice of five settings to suit local water hardness. This allows optimum metered quantities of anti-scaler and corrosion inhibitor to be added to the water supply, and prevents the buildup of lime scale on the heater coil. Operating data can be called up any time, allowing you to make continual adjustments.

Time-proven burner technology with new turbo fan

- Kärcher burner technology not only translates to more economical operation, but also makes our hot water pressure washers trendsetters in environmental protection thanks to their low emissions and highly efficient operation.

Technical data

Model	Part No.	GPM	PSI	Drive	HP	Electrical	Amps	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HDS 5.0/30-4S Eb	1.071-919.0	2.4-5.0	460-3000	Direct	11	208-240V / 3ph	27	Kärcher Axial	516	51 x 32 x 45
HDS 5.0/30-4S Ec	1.071-920.0	2.4-5.0	460-3000	Direct	11	460-480V / 3ph	15	Kärcher Axial	516	51 x 32 x 45

Accessories

	Order No.	Description
■	4.118-005.0 ■	EASY!Force trigger gun (German model) - zero force required.
■	4.112-000.0 ■	41" spray lance
■	6.110-029.0 ■	50' EASY!Lock Longlife hose with ANTI!Twist connection
■	2.113-012.0 ■	Power nozzle, 062
□	4.111-041.0 ■	Adapter for EASY!Force trigger gun connecting to 3/8" hose
□	8.918-280.0	Hose, 3/8" x 6'
□	4.118-009.0 ■	Servo control

■ Included □ Optional

■ Compatible with EASY!Lock

HDS SPECIAL CLASS

The zero emission specialist.

The emission-free HDS-E 3.3/25-4M Ec with electric heater is ideal where exhaust gases are undesirable or prohibited. Thanks to the unique type of heater insulation and Kärcher eco!efficiency mode, the HDS-E 3.3/25-4M Ec is efficient and eco-friendly. Models are ETL certified to UL & CSA safety standards.

Efficiency

- eco!efficiency mode – economical and environmentally friendly, even during longer periods of use.

Ease of use

- Intuitive operation with large single-button selector switch.

Technical data

Model	Part No.	GPM	PSI	Drive	HP	Electrical	Amps	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HDS-E 3.3/25-4M Ec	1.030-902.0	1.6-3.3	465-2520	Direct	7.5	460V / 3ph	31	Kärcher Axial	290	50 x 32 x 45
HDS-E 3.3/25-4M Ef	1.030-903.0	1.6-3.3	465-2520	Direct	7.5	575V / 3ph	28	Kärcher Axial	352	50 x 32 x 45

Accessories

	Order No.	Description
■	4.118-005.0 ■	EASY!Force trigger gun (German model) - zero force required.
■	4.112-000.0 ■	41" spray lance
■	6.110-030.0 ■	50' EASY!Lock hose with ANTI!Twist connection
■	2.113-009.0 ■	Power nozzle, 047
□	2.111-013.0 ■	Surface cleaner, FR 30 ME
□	4.111-037.0 ■	Coupler
□	4.118-007.0 ■	Servo Control
□	4.111-036.0 ■	Adapter for EASY!Lock lance connecting to M18 Dirtblaster nozzle
□	4.111-041.0 ■	Adapter for EASY!Force gun connecting to 3/8" hose

■ Included □ Optional

■ Compatible with EASY!Lock

HDS CAGE

Rugged operations.

Built on a rugged 1-1/4" powder coated steel frame, these compact electric roll cage models are designed for construction sites, farms and factories where electricity is available. The three models deliver hot water cleaning of up to 2000 PSI using 120V or 230V/1ph. Each features a Kärcher direct-drive crankcase-style pump with limited 7-year warranty, industrial-grade motor and flat-free tires.

Durable design

- 50 ft. of durable, wire braid hose rated for 3000 PSI and with hose guard for burst.
- Safety relief valve attached to discharge side for protection against excess pressure build up.

Smart features

- Easy-to-attach downstream detergent injection with quick couplers and brass soap nozzle.
- Fuel filter/water separator ensures pure fuel supply.
- EASY!Force gun with cruise control like technology - uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use.

Technical data

Model	Part No.	GPM	PSI	Drive	HP	Electrical	Amps	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HDS 2.0/10 Ed Cage	1.575-511.0	2.1	1000	Direct	1.5	120V / 1ph	15	Kärcher KF	480	50 x 40 x 50
HDS 1.9/15 Ed Cage	1.575-512.0	1.9	1500	Direct	2	120V / 1ph	20	Kärcher KF	480	50 x 40 x 50
HDS 3.5/20 Ea Cage	1.575-513.0	3.5	2000	Direct	5	230V / 1ph	22	Kärcher KF	500	50 x 40 x 50

Accessories

	Order No.	Description
■	8.756-481.0 ■	EASY!Force trigger gun (North American Model) - zero force required. Standard 1/4" connection for wand, 3/8" connection for hose.

Options (factory installed)

☐	9.801-024.0	100' EZEE hose reel kit (hose not Included)
☐	9.804-570.0	100' Pivot hose reel kit (hose not Included)

■ Included ☐ Optional ■ Please note: NOT compatible with EASY!Lock.

For more information, contact Lorchem Technologies at:
(800) 788-8867 • info@lorchem.com • www.lorchem.com

HDS HAND TRUCK

Heavy-duty output.

Kärcher's North American hand truck design features heavy-gauge 1 1/4" steel frame with powder coat finish and a high pressure rupture disc rated to 7000 lbs to protect the operator against injury. Units come with belt-drive Kärcher crankcase pumps. All models are ETL certified to UL and CSA safety standards.

Smart features

- Cast iron pulley system with OSHA-compliant, totally enclosed belt guard, and easy-to-adjust belt tension (belt-drive models).
- Water resistant control box, burner on/off switch and adjustable thermostat.
- EASY!Force gun with cruise control like technology - uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use.

Technical Data

Model	Part No.	GPM	PSI	Drive	HP	Electrical	Amps	Pump	Weight (lbs)	Dimensions (L x W x H) inches
HDS 3.9/20 Ea	1.575-505.0	3.9	2000	Belt	6	230V / 1ph	29	Kärcher KM	660	49 x 40 x 50
HDS 3.5/30 Ea	1.575-508.0	3.5	3000	Belt	7.5	230V / 1ph	36	Kärcher KM	690	49 x 40 x 50
HDS 3.5/30 Eb	1.575-509.0	3.5	3000	Belt	7.5	230V / 3ph	25	Kärcher KM	605	49 x 40 x 50
HDS 3.5/30 Ec	1.575-510.0	3.5	3000	Belt	7.5	460V / 3ph	13	Kärcher KM	605	49 x 40 x 50

Accessories

	Order No.	Description
■	8.756-481.0 ■	EASY!Force trigger gun (North American Model) - zero force required. Standard 1/4" connection for wand, 3/8" connection for hose.

Options (factory installed)

☐	9.801-008.0	Float tank (6-7.5 HP units, with soap valve)
☐	9.801-006.0	Auto start/stop (6-7.5 HP models)
☐	9.804-512.0	Auto start/stop and steam combo (6-7.5 HP models)
☐	9.804-512.0	Auto start/stop and float tank (6-7.5 HP models)
☐	9.804-514.0	Auto start/stop, steam and float tank (6-7.5 HP models)
☐	9.804-515.0	Steam combination (6-7 HP, with float tank)
☐	9.801-009.0	Steam combination (6-7 HP, without float tank)
☐	9.801-001.0	Time delay

Time delay shutdown and auto start/stop are mutually exclusive

Options (field installed)

☐	8.739-132.0	Kärcher Tuff-Flex, 1-wire, 3/8" ID, 100', 3000 PSI, 275°
☐	9.801-023.0	100' EZEE hose reel kit (hose not Included)

■ Included ☐ Optional

■ Please note: NOT compatible with EASY!Lock.

HDS CABINET

Cleaning technology for indoors.

This Kärcher all-electric hot water pressure washer introduces hot-water tank technology to deliver hot water on demand ideal for indoor cleaning. Water is heated by flowing through a coil inside an 80-gallon water tank. Heating elements generate 138,000 BTU to produce hot water of up to 180°F. Both models are ETL and CSA certified.

Durable design

- Heavy-duty, steel cabinets are protected by an epoxy powder coat finish; upper cabinet ventilated for cool operation
- Thermal pump saver valve prevents damage by venting recirculated water
- Low-water flow switch prevents damage to heating elements due to lack of water.

Smart features

- Easy-to-attach detergent injector and four quick couplers nozzles.
- Auto start function allows unit to be turned on with pull of the trigger.
- EASY!Force gun with cruise control like technology - uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use.

Technical data

Model	Part No.	GPM	PSI	Drive	HP	Electrical	Amps	Pump	Weight (lbs)	Dimensions (L x W x H) inches
HDS 4.0/20 E Ec	1.109-075.0	4.2	2000	Belt	6.2	460V / 3ph	55	Kärcher KM	640	32 x 24 x 52
HDS 4.0/30 E Ec	1.109-076.0	3.5	3000	Belt	7.5	460V / 3ph	59	Kärcher KM	640	32 x 24 x 52
HDS 4.0/20 E Ef	1.109-956.0	3.5	2000	Belt	5	575V / 3ph	46	Kärcher KM	620	34 x 25 x 52
HDS 4.0/30 E Ef	1.109-957.0	3.5	3000	Belt	7.5	575V / 3ph	49	Kärcher KM	640	34 x 25 x 52

Accessories

	Order No.	Description
■	8.756-481.0 ■	EASY!Force trigger gun (North American Model) - zero force required. Standard 1/4" connection for wand, 3/8" connection for hose.

Options (factory installed)

	Order No.	Description
☐	9.801-012.0	Time delay shutdown (replaces auto start-stop) (only for 460V units)
☐	9.801-002.0	Pressure washer stainless steel cabinet (only for 460V units)

■ Included ☐ Optional *Existing options only for 460V units. ■ Please note: NOT compatible with EASY!Lock.

For more information, contact Lorchem Technologies at:
(800) 788-8867 • info@lorchem.com • www.lorchem.com

HDS STATIONARY - NG / LP

Innovation inside and out.

The innovative, rugged design of the new Kärcher Classic HDS natural gas and LP-heated cabinet pressure washer delivers up to 5 gpm at 3,000 psi of industrial power. Built in the U.S.A., each model is constructed with anodized structural rivets, a water cooled electric motor, standard auto start/stop and Kärcher's axial direct-drive pump backed by a 7-year warranty. All models are ETL certified to UL and CSA safety standards.

Smart features

- Integrated RM 110 reservoir and steam stage
- Inlet/outlet connections can be easily moved to either side of the unit.
- Auto start-stop for on-demand cleaning
- EASY!Force gun with cruise control like technology - uses its own recoil force to hold the trigger down.
- "Stay-in-Place" ignition pilot light with swing out burner ring
- Cool wall cabinet construction
- Pulsation damper

Technical data

Natural Gas	Part No.	GPM	PSI	Drive	Electrical	Amps	Pump / RPM	HP	Weight (lbs)	BTU	Dimensions (L x W x H)
HDS 3.5/23 Eg ST NG	1.109-797.0	3.5	2300	Direct	208V / 1ph	26	Kärcher Axial / 1725	8.1	695	310000	49 x 24 x 48
HDS 4.5/22 Ea ST NG	1.109-722.0	4.5	2200	Direct	230V / 1ph	30	Kärcher Axial / 1725	9.5	695	393000	49 x 24 x 48
HDS 3.5/30 Ea ST NG	1.109-729.0	3.5	3000	Direct	230V / 1ph	27	Kärcher Axial / 1725	9.5	695	310000	49 x 24 x 48
HDS 5.0/30 Eb ST NG	1.109-742.0	5	3000	Direct	230V / 3ph	27	Kärcher Axial / 1725	11	700	398000	49 x 24 x 48
HDS 5.0/30 Ec St NG	1.109-743.0	5	3000	Direct	460V / 3ph	19	Kärcher Axial / 1725	11	700	398000	49 x 24 x 48

LP gas-heated	Part No.	GPM	PSI	Drive	Electrical	Amps	Pump / RPM	HP	Weight (lbs)	BTU	Dimensions (L x W x H)
HDS 3.5/23 Eg ST LP	1.109-798.0	3.5	2300	Direct	208V / 1ph	26	Kärcher Axial / 1725	8.1	695	310000	49 x 24 x 48
HDS 4.5/22 Ea ST LP	1.109-763.0	4.5	2200	Direct	230V / 1ph	30	Kärcher Axial / 1725	9.5	695	393000	49 x 24 x 48
HDS 3.5/30 Ea ST LP	1.109-770.0	3.5	3000	Direct	230V / 1ph	27	Kärcher Axial / 1725	9.5	695	310000	49 x 24 x 48
HDS 5.0/30 Eb ST LP	1.109-783.0	5	3000	Direct	230V / 3ph	27	Kärcher Axial / 1725	11	700	398000	49 x 24 x 48
HDS 5.0/30 Ec St LP	1.109-784.0	5	3000	Direct	460V / 3ph	19	Kärcher Axial / 1725	11	700	398000	49 x 24 x 48

Accessories

	Order No.	Description
■	4.118-005.0 ■	EASY!Force trigger gun (German model) - zero force required.
☐	2.744-008.0	Remote Kit single station
☐	6.685-195.0	Chemical solenoid valve (brass) for use with remote kit
☐	8.708-846.0	Chemical solenoid valve (stainless steel) for use with remote kit
☐	9.801-040.0	Draft diverter, 10"
☐	8.753-474.0	Damper, draft 10"
☐	8.739-130.0	Kärcher Tuff-Flex, 1-wire, 3/8" ID, 50', 3000 PSI, 275°
☐	2.639-919.0	Self-winding hose reel, 66'
☐	2.639-931.0	Swivel wall mount bracket
☐	8.923-213.0	Hot water discharge outlet relocation

■ Included ☐ Optional ■ Compatible with EASY!Lock

For more information, contact Lorchem Technologies at:
(800) 788-8867 • info@lorchem.com • www.lorchem.com

HDS STATIONARY - NG / LP - NORTH AMERICAN

High cleaning performance.

The Liberty Kärcher HDS natural gas and LP-heated cabinet pressure washer delivers up to 9.5 gpm at 3000 psi of industrial power. Built in the U.S.A., each model is constructed with anodized structural rivets, industrial motors and Kärcher pumps that are backed by a 7-year warranty.



Easy to service and operate

- All-access cabinet design with six lift out panels and easy lock fasteners provides easy access to components for maintenance in tight situations.
- Swing-out cast iron burner ring with separate “stay-in-place” ignition pilot light allows easy access and removal of the burner ring.

Smart Engineering

- Improved “Stay-Tite” belt tensioning system maintains belt tension on the pump with a torsion bar for precise tension adjustment.
- The heating coil is made of leak-free, cold rolled, schedule 80 steel pipe and is wrapped with a thick foil blanket insulation that keeps cabinet walls cool to the touch.
- EASY!Force gun with cruise control like technology - uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use.

Accessories

	Order No.	Description
■	8.756-481.0 ■	EASY!Force trigger gun (North American Model) - zero force required. Standard 1/4" connection for wand, 3/8" connection for hose.
□	8.917-509.0	Kit, wireless remote pump/burner/detergent
□	8.921-832.0	Wireless hand-held transmitter
□	8.917-817.0	Kit, wall bracket wireless transmitter
□	8.921-774.0	NG kit, wired remote station - pump and burner
□	8.921-773.0	NG kit, wired remote detergent
□	8.922-157.0	Remote control box (wired) (Pump / burner switch Included, add 8.921-773.0 for detergent switch). For additional remote only.
□	8.917-507.0	Snap-N-Go Auto Start/Stop Kit w/ Lock Out (no remote, requires 8.917-509.0)
□	9.807-646.0	Snap-N-Go Auto Start/Stop Kit w/o Lock Out (wired remote, requires 8.921-774.0)
□	8.917-508.0	Snap-N-Go Time Delay Kit
□	8.921-776.0	Kit, steam combo
□	9.801-040.0	Draft diverter, 10”, up to 5 gpm
□	8.717-730.0	Draft diverter, 12”, over 5 gpm
□	8.753-474.0	Draft damper, 10”
□	8.753-478.0	Draft damper, 12”
□	8.753-706.0	Reducer, stack 12” to 10”
□	8.753-707.0	Reducer, stack 10” to 8”
□	8.923-213.0	Outlet relocator

■ Included □ Optional ■ Please note: NOT compatible with EASY!Lock.

For more information, contact Lorchem Technologies at:
(800) 788-8867 • info@lorchem.com • www.lorchem.com

HDS STATIONARY - NG

Natural gas-heated 3.5-5 GPM medium cabinet design

Model	Part No.	GPM	PSI	Drive	Electrical	Amps	Pump / RPM	HP	Weight (lbs)	BTU	Dimensions (L x W x H)
HDS 3.5/20 Ea ST NG	1.109-715.0	3.5	2000	Belt	230V / 1ph	25	KD4020R / 1350	5	815	320000	49 x 24 x 48
HDS 4.0/22 Ea ST NG	1.109-716.0	4	2200	Belt	230V / 1ph	29	KM4035R / 1250	6.2	843	364000	49 x 24 x 48
HDS 4.0/22 Eb ST NG	1.109-717.0	4	2200	Belt	230V / 3ph	16	KM4035R / 1250	6.2	843	364000	49 x 24 x 48
HDS 4.0/22 Ec ST NG	1.109-718.0	4	2200	Belt	460V / 3ph	7	KM4035R / 1250	6.2	843	364000	49 x 24 x 48
HDS 4.0/22 Ef ST NG	1.109-719.0	4	2200	Belt	575V / 3ph	6.5	KM4035R / 1250	6.2	843	364000	49 x 24 x 48
HDS 4.0/22 Eg ST NG	1.109-720.0	4	2200	Belt	208V / 1ph	30	KM4035R / 1250	6.2	843	364000	49 x 24 x 48
HDS 4.0/22 Eh ST NG	1.109-721.0	4	2200	Belt	208V / 3ph	18	KM4035R / 1250	6.2	843	364000	49 x 24 x 48
HDS 3.9/30 Ea ST NG	1.109-723.0	3.9	3000	Belt	230V / 1ph	36	KM4035R / 1225	8.2	856	354000	49 x 24 x 48
HDS 3.9/30 Eb ST NG	1.109-724.0	3.9	3000	Belt	230V / 3ph	25	KM4035R / 1225	8.2	856	354000	49 x 24 x 48
HDS 3.9/30 Ec ST NG	1.109-725.0	3.9	3000	Belt	460V / 3ph	11	KM4035R / 1225	8.2	856	354000	49 x 24 x 48
HDS 3.9/30 Ef ST NG	1.109-726.0	3.9	3000	Belt	575V / 3ph	14	KM4035R / 1225	8.2	856	354000	49 x 24 x 48
HDS 3.9/30 Eg ST NG	1.109-727.0	3.9	3000	Belt	208V / 1ph	38	KM4035R / 1225	8.2	856	354000	49 x 24 x 48
HDS 3.9/30 Eh ST NG	1.109-728.0	3.9	3000	Belt	208V / 3ph	27	KM4035R / 1225	8.2	856	354000	49 x 24 x 48
HDS 5.0/23 Ea ST NG	1.109-730.0	5.0	2300	Belt	230V / 1ph	36	KT6035R / 1225	8.2	856	439000	49 x 24 x 48
HDS 5.0/23 Eb ST NG	1.109-731.0	5.0	2300	Belt	230V / 3ph	25	KT6035R / 1225	8.2	856	439000	49 x 24 x 48
HDS 5.0/23 Ec ST NG	1.109-732.0	5.0	2300	Belt	460V / 3ph	11	KT6035R / 1225	8.2	856	439000	49 x 24 x 48
HDS 5.0/23 Ef ST NG	1.109-733.0	5.0	2300	Belt	575V / 3ph	14	KT6035R / 1225	8.2	856	439000	49 x 24 x 48
HDS 5.0/23 Eg ST NG	1.109-734.0	5.0	2300	Belt	208V / 1ph	38	KT6035R / 1225	8.2	856	439000	49 x 24 x 48
HDS 5.0/23 Eh ST NG	1.109-735.0	5.0	2300	Belt	208V / 3ph	27	KT6035R / 1225	8.2	856	439000	49 x 24 x 48
HDS 4.8/30 Ea ST NG	1.109-736.0	4.8	3000	Belt	230V / 1ph	42	KT6035R / 1225	10	885	415000	49 x 24 x 48
HDS 4.8/30 Eb ST NG	1.109-737.0	4.8	3000	Belt	230V / 3ph	26	KT6035R / 1225	10	885	415000	49 x 24 x 48
HDS 4.8/30 Ec ST NG	1.109-738.0	4.8	3000	Belt	460V / 3ph	15	KT6035R / 1225	10	885	415000	49 x 24 x 48
HDS 4.8/30 Ef ST NG	1.109-739.0	4.8	3000	Belt	575V / 3ph	14	KT6035R / 1225	10	885	415000	49 x 24 x 48
HDS 4.8/30 Eg ST NG	1.109-740.0	4.8	3000	Belt	208V / 1ph	49	KT6035R / 1225	10	885	415000	49 x 24 x 48
HDS 4.8/30 Eh ST NG	1.109-741.0	4.8	3000	Belt	208V / 3ph	32	KT6035R / 1225	10	885	415000	49 x 24 x 48

Natural gas-heated 6.3+ GPM large cabinet design

Model	Part No.	GPM	PSI	Drive	Electrical	Amps	Pump / RPM	HP	Weight (lbs)	BTU	Dimensions (L x W x H)
HDS 6.3/32 Eb ST NG	1.109-744.0	6.3	3200	Belt	230V / 3ph	39	KT6035R / 1625	15	1825	507000	64 x 35 x 61
HDS 6.3/32 Ec ST NG	1.109-745.0	6.3	3200	Belt	460V / 3ph	19	KT6035R / 1625	15	1825	507000	64 x 35 x 61
HDS 6.3/32 Ef ST NG	1.109-746.0	6.3	3200	Belt	575V / 3ph	18	KT6035R / 1625	15	1825	507000	64 x 35 x 61
HDS 6.3/32 Eh ST NG	1.109-747.0	6.3	3200	Belt	208V / 3ph	39	KT6035R / 1625	15	1825	507000	64 x 35 x 61
HDS 8.0/32 Eb ST NG	1.109-748.0	8.0	3200	Belt	230V / 3ph	46	KX9536R / 1458	20	1840	658000	64 x 35 x 61
HDS 8.0/32 Ec ST NG	1.109-749.0	8.0	3200	Belt	460V / 3ph	26	KX9536R / 1458	20	1840	658000	64 x 35 x 61
HDS 8.0/32 Ef ST NG	1.109-750.0	8.0	3200	Belt	575V / 3ph	21	KX9536R / 1458	20	1840	658000	64 x 35 x 61
HDS 8.0/32 Eh ST NG	1.109-751.0	8.0	3200	Belt	208V / 3ph	60	KX9536R / 1458	20	1840	658000	64 x 35 x 61
HDS 9.5/30 Eb ST NG	1.109-752.0	9.5	3000	Belt	230V / 3ph	52	KX1036R / 1650	20	1910	816000	64 x 35 x 61
HDS 9.5/30 Ec ST NG	1.109-753.0	9.5	3000	Belt	460V / 3ph	26	KX1036R / 1650	20	1910	816000	64 x 35 x 61
HDS 9.5/30 Ef ST NG	1.109-754.0	9.5	3000	Belt	575V / 3ph	21	KX1036R / 1650	20	1910	816000	64 x 35 x 61
HDS 9.5/30 Eh ST NG	1.109-755.0	9.5	3000	Belt	208V / 3ph	30	KX1036R / 1650	20	1910	816000	64 x 35 x 61

HDS STATIONARY - LP

LP gas-heated 3.5-5 GPM medium cabinet design

Model	Part No.	GPM	PSI	Drive	Electrical	Amps	Pump / RPM	HP	Weight (lbs)	BTU	Dimensions (L x W x H)
HDS 3.5/20 Ea ST LP	1.109-756.0	3.5	2000	Belt	230V / 1ph	25	KD4020R / 1350h	5	815	320000	49 x 24 x 48
HDS 4.0/22 Ea ST LP	1.109-757.0	4	2200	Belt	230V / 1ph	29	KM4035R / 1250	6.2	843	364000	49 x 24 x 48
HDS 4.0/22 Eb ST LP	1.109-758.0	4	2200	Belt	230V / 3ph	16	KM4035R / 1250	6.2	843	364000	49 x 24 x 48
HDS 4.0/22 Ec ST LP	1.109-759.0	4	2200	Belt	460V / 3ph	7	KM4035R / 1250	6.2	843	364000	49 x 24 x 48
HDS 4.0/22 Ef ST LP	1.109-760.0	4	2200	Belt	575V / 3ph	6.5	KM4035R / 1250	6.2	843	364000	49 x 24 x 48
HDS 4.0/22 Eg ST LP	1.109-761.0	4	2200	Belt	208V / 1ph	30	KM4035R / 1250	6.2	843	364000	49 x 24 x 48
HDS 4.0/22 Eh ST LP	1.109-762.0	4	2200	Belt	208V / 3ph	18	KM4035R / 1250	6.2	843	364000	49 x 24 x 48
HDS 3.9/30 Ea ST LP	1.109-764.0	3.9	3000	Belt	230V / 1ph	36	KM4035R / 1225	8.2	856	354000	49 x 24 x 48
HDS 3.9/30 Eb ST LP	1.109-765.0	3.9	3000	Belt	230V / 3ph	25	KM4035R / 1225	8.2	856	354000	49 x 24 x 48
HDS 3.9/30 Ec ST LP	1.109-766.0	3.9	3000	Belt	460V / 3ph	11	KM4035R / 1225	8.2	856	354000	49 x 24 x 48
HDS 3.9/30 Ef ST LP	1.109-767.0	3.9	3000	Belt	575V / 3ph	14	KM4035R / 1225	8.2	856	354000	49 x 24 x 48
HDS 3.9/30 Eg ST LP	1.109-768.0	3.9	3000	Belt	208V / 1ph	38	KM4035R / 1225	8.2	856	354000	49 x 24 x 48
HDS 3.9/30 Eh ST LP	1.109-769.0	3.9	3000	Belt	208V / 3ph	27	KM4035R / 1225	8.2	856	354000	49 x 24 x 48
HDS 5.0/23 Ea ST LP	1.109-771.0	5.0	2300	Belt	230V / 1ph	36	KT6035R / 1225	8.2	856	439000	49 x 24 x 48
HDS 5.0/23 Eb ST LP	1.109-772.0	5.0	2300	Belt	230V / 3ph	25	KT6035R / 1225	8.2	856	439000	49 x 24 x 48
HDS 5.0/23 Ec ST LP	1.109-773.0	5.0	2300	Belt	460V / 3ph	11	KT6035R / 1225	8.2	856	439000	49 x 24 x 48
HDS 5.0/23 Ef ST LP	1.109-774.0	5.0	2300	Belt	575V / 3ph	14	KT6035R / 1225	8.2	856	439000	49 x 24 x 48
HDS 5.0/23 Eg ST LP	1.109-775.0	5.0	2300	Belt	208V / 1ph	38	KT6035R / 1225	8.2	856	439000	49 x 24 x 48
HDS 5.0/23 Eh ST LP	1.109-776.0	5.0	2300	Belt	208V / 3ph	27	KT6035R / 1225	8.2	856	439000	49 x 24 x 48
HDS 4.8/30 Ea ST LP	1.109-777.0	4.8	3000	Belt	230V / 1ph	42	KT6035R / 1225	10	885	415000	49 x 24 x 48
HDS 4.8/30 Eb ST LP	1.109-778.0	4.8	3000	Belt	230V / 3ph	26	KT6035R / 1225	10	885	415000	49 x 24 x 48
HDS 4.8/30 Ec ST LP	1.109-779.0	4.8	3000	Belt	460V / 3ph	15	KT6035R / 1225	10	885	415000	49 x 24 x 48
HDS 4.8/30 Ef ST LP	1.109-780.0	4.8	3000	Belt	575V / 3ph	14	KT6035R / 1225	10	885	415000	49 x 24 x 48
HDS 4.8/30 Eg ST LP	1.109-781.0	4.8	3000	Belt	208V / 1ph	49	KT6035R / 1225	10	885	415000	49 x 24 x 48
HDS 4.8/30 Eh ST LP	1.109-782.0	4.8	3000	Belt	208V / 3ph	32	KT6035R / 1225	10	885	415000	49 x 24 x 48

LP gas-heated 6.3+ GPM large cabinet design

Model	Part No.	GPM	PSI	Drive	Electrical	Amps	Pump / RPM	HP	Weight (lbs)	BTU	Dimensions (L x W x H)
HDS 6.3/32 Eb ST LP	1.109-785.0	6.3	3200	Belt	230V / 3ph	39	KT6035R / 1625	15	1825	507000	64 x 35 x 61
HDS 6.3/32 Ec ST LP	1.109-786.0	6.3	3200	Belt	460V / 3ph	19	KT6035R / 1625	15	1825	507000	64 x 35 x 61
HDS 6.3/32 Ef ST LP	1.109-787.0	6.3	3200	Belt	575V / 3ph	18	KT6035R / 1625	15	1825	507000	64 x 35 x 61
HDS 6.3/32 Eh ST LP	1.109-788.0	6.3	3200	Belt	208V / 3ph	39	KT6035R / 1625	15	1825	507000	64 x 35 x 61
HDS 8.0/32 Eb ST LP	1.109-789.0	8.0	3200	Belt	230V / 3ph	46	KX9536R / 1458	20	1840	658000	64 x 35 x 61
HDS 8.0/32 Ec ST LP	1.109-790.0	8.0	3200	Belt	460V / 3ph	26	KX9536R / 1458	20	1840	658000	64 x 35 x 61
HDS 8.0/32 Ef ST LP	1.109-791.0	8.0	3200	Belt	575V / 3ph	21	KX9536R / 1458	20	1840	658000	64 x 35 x 61
HDS 8.0/32 Eh ST LP	1.109-792.0	8.0	3200	Belt	208V / 3ph	60	KX9536R / 1458	20	1840	658000	64 x 35 x 61
HDS 9.5/30 Eb ST LP	1.109-793.0	9.5	3000	Belt	230V / 3ph	52	KX1036R / 1650	20	1910	775000	64 x 35 x 61
HDS 9.5/30 Ec ST LP	1.109-794.0	9.5	3000	Belt	460V / 3ph	26	KX1036R / 1650	20	1910	775000	64 x 35 x 61
HDS 9.5/30 Ef ST LP	1.109-795.0	9.5	3000	Belt	575V / 3ph	21	KX1036R / 1650	20	1910	775000	64 x 35 x 61
HDS 9.5/30 Eh ST LP	1.109-796.0	9.5	3000	Belt	208V / 3ph	60	KX1036R / 1650	20	1910	775000	64 x 35 x 61

HDS P/PE CAGE

Outstanding on all terrains.

Built on a rugged 1-1/4" powder coated steel frame, these compact gas roll cage models are designed for construction sites, farms and factories. The different models deliver hot water cleaning of up to 3500 PSI. Each features a Kärcher pump with limited 7-year warranty, industrial-grade motor and flat-free tires.

ETL LISTED · 7 YEAR PUMP WARRANTY · EASY!Force · FLAT FREE TIRES · E-Start · POWERED by HONDA

Durable design

- Flat-free tires
- 7-year pump warranty

Smart features

- EASY!Force gun with cruise control like technology - uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use.
- ETL certified to UL & CSA Safety Standards

Technical data

Model	Part No.	GPM	PSI	Drive	CC	Engine	Start	Pump	Burner	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HDS 2.6/30 P Cage	1.575-550.0	3.0	3000	Direct	270	Honda GX270	Recoil	Kärcher KP	12V DC	500	50 x 40 x 58
HDS 3.5/30 P Cage	1.575-551.0	3.5	3000	Direct	337	Honda GX340	Recoil	Kärcher KS	12V DC	550	50 x 40 x 58
HDS 3.5/30 Pe Cage	1.575-552.0	3.5	3000	Direct	337	Honda GX340	Electric	Kärcher KS	12V DC	560	50 x 40 x 58
HDS 3.5/35 Pe Cage	1.575-553.0	3.5	3500	Direct	389	Honda GX390	Electric	Kärcher KS	12V DC	595	50 x 40 x 58

Accessories

	Order No.	Description
■	8.756-481.0 ■	EASY!Force trigger gun (North American Model) - zero force required. Standard 1/4" connection for wand, 3/8" connection for hose.

■ Included ☐ Optional ■ Please note: NOT compatible with EASY!Lock.

HDS PE CAGE

Optimum performance at remote locations.

These durable, skid-mounted models are designed for optimum cleaning performance at remote locations and feature Kärcher's unique 12V downdraft burner system. The highly compact burner is more than 92% efficient, resulting in better heat transfer using much less fuel. They feature belt-drive crankcase-style pumps. Certified to UL and CSA safety standards.

Durable design

- Industrial-duty, tri-plunger, oil-bath, belt-drive Kärcher KT pump with 7-year warranty, brass pump head, and Tru-Trak belt adjustments; operates at a low RPM for low-maintenance operation and long life.
- Proprietary scale inhibiting system prevents build-up of mineral deposits inside the coil.
- Rust-free 11 gallon Polyethylene diesel and gasoline tanks for hours of uninterrupted operation.
- Infinitely variable operating pressure, water volume, temperature control, and detergent metering.
- Kärcher's 92% efficient top-fired burner delivers more heat from less fuel for the lowest operating costs in the industry.
- Kärcher safety features include pressure switches, rupture disk, low-water and low-fuel protection that shuts down burner when incoming water and fuel are insufficient or interrupted.
- EASY!Force gun with cruise control like technology - uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use.

Technical data

Model	Part No.	GPM	PSI	Drive	CC	Engine	Fuel	Pump	Weight (lbs)	Dimensions (L x W x H) inches
HDS 4.0/32 Pe Cage	1.575-615.0	4.0	3200	Belt	389	Honda GX390	Gas	Kärcher KT	692	51 x 33 x 43
HDS 5.5/35 Pe Cage	1.575-617.0	5.5	3500	Belt	688	Honda GX630	Gas	Kärcher KT	741	51 x 33 x 43

Accessories

	Order No.	Description
■	4.118-005.0 ■	EASY!Force trigger gun (German model) - zero force required.
■	4.112-000.0 ■	41" spray lance
■	6.110-029.0 ■	50' EASY!Lock Longlife hose with ANTI!Twist connection
■	2.113-022.0 ■	Power Nozzle 25045 (Fits HDS 4.0/32 Pe Cage)
■	2.113-026.0 ■	Power Nozzle 25060 (Fits HDS 5.5/35 Pe Cage)
□	4.111-041.0 ■	Adapter for EASY!Force trigger gun connecting to 3/8" hose

■ Included □ Optional ■ Compatible with EASY!Lock

For more information, contact Lorchem Technologies at:
(800) 788-8867 • info@lorchem.com • www.lorchem.com

HDS PE/DE CAGE

The industrial workhorse.

Kärcher Series oil-fired skids are the workhorses of the pressure washer industry. Delivering up to 8.0 GPM of hot water and up to 3500 PSI, these rugged gas and diesel-powered machines are built on an open frame using heavy-gauge 1-1/4" powder coated steel and are ideal for mounting in a truck or on a trailer. The electric-start engine and powerful belt-drive Kärcher KT and KX pumps are isolated from the rest of the machine on a shock-mounted sub-frame to reduce vibration. Steam combination comes standard with all models.

ETL LISTED · 7 YEAR PUMP WARRANTY · EASY!Force · POWERED by HONDA

Reliable and durable

- Honda, Vanguard and Kubota engines with electric start
- Kärcher belt-drive tri-plunger pumps with 7-year warranty
- EASY!Force gun with cruise control like technology - uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use.

Technical data

Model	Part No.	GPM	PSI	Drive	CC	Engine	Fuel	Pump	Burner	Ship Weight (lbs)	Ship Dimensions (L x W x H)
HDS 3.9/30 Pe Cage	1.575-600.0	3.9	3000	Belt	389	Honda GX390	Gas	Kärcher KT	12V DC	790	54 x 56 x 55
HDS 4.8/30 Pe Cage	1.575-601.0	4.8	3000	Belt	479	Vanguard 18	Gas	Kärcher KT	12V DC	800	54 x 56 x 55
HDS 4.8/30 Pe Cage	1.575-602.0	4.8	3000	Belt	479	Vanguard 18	Gas	Kärcher KT	120V AC	945	54 x 56 x 55
HDS 4.7/35 Pe Cage	1.575-603.0	4.7	3500	Belt	688	Honda GX630	Gas	Kärcher KT	12V DC	855	54 x 56 x 55
HDS 4.7/35 Pe Cage	1.575-604.0	4.7	3500	Belt	688	Honda GX630	Gas	Kärcher KT	120V AC	890	54 x 56 x 55
HDS 5.6/35 Pe Cage	1.575-605.0	5.6	3500	Belt	688	Honda GX660	Gas	Kärcher KT	12V DC	852	54 x 56 x 55
HDS 5.6/35 Pe Cage	1.575-606.0	5.6	3500	Belt	688	Honda GX660	Gas	Kärcher KT	120V AC	970	54 x 56 x 55
HDS 5.6/35 De Cage	1.110-622.0	5.4	3500	Belt	1123	Kubota D1105-E3B	Diesel	Kärcher KT	12V DC	1214	54 x 56 x 55
HDS 5.6/35 De Cage	1.110-623.0	5.4	3500	Belt	1123	Kubota D1105-E3B	Diesel	Kärcher KT	120V AC	1300	54 x 56 x 55
HDS 8.0/30 Ge Cage	1.575-611.0	8.0	3000	Belt	688	Honda GX660	Gas	Kärcher KX	12V DC	805	54 x 56 x 55
HDS 8.0/30 Ge Cage	1.575-612.0	8.0	3000	Belt	688	Honda GX660	Gas	Kärcher KX	120V AC	865	54 x 56 x 55

Accessories

	Order No.	Description
■	8.756-481.0 ■	EASY!Force trigger gun (North American Model) - zero force required. Standard 1/4" connection for wand, 3/8" connection for hose.

Options (factory installed)

	Order No.	Description
□	8.903-430.0	Stackless flue adapter

Options (field installed)

	Order No.	Description
□	8.904-051.0	Battery installed on Honda GX630 and GX660 models only

■ Included □ Optional ■ Please note: NOT compatible with EASY!Lock.

For more information, contact Lorchem Technologies at:
(800) 788-8867 · info@lorchem.com · www.lorchem.com

TULE SERIES HDS 3.5/40 GE MT

Towable and maneuverable hot water pressure washer.

Ready to pick up and go at a moments notice, Kärcher's Tule Series HDS 3.5/40 Ge MT hot water pressure washer trailer provides the necessary cleaning power on virtually any job site which has a water source. Simply unhitch the Tule Series HDS 3.5/40 Ge MT and take the cleaning power where you need it most. The Tule Series trailer features a reliable Honda engine, 8 gallon diesel fuel tank, electric start with manual start backup and much more.

U.S. Design Patent No. 9,724,734 B2

Smart and reliable

- Honda GX 390 engine and electric start with manual start backup
- Adjustable thermostat for water temperature regulation
- 8 gallon diesel fuel tank
- Lift handle and swing away tongue for easier hook up of the trailer and storage
- EASY!Force gun with cruise control like technology - uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use.

Technical Data

Model	Part No.	GPM	PSI	Drive	Burner	Engine	Start	Pump	Ship weight (lbs)	Dimensions (L x W x H) inches
HDS 3.5/40 Ge MT	1.103-844.0	3.5	4000	Direct	12V / DC	Honda GX390	Electric*	Kärcher KS	1000	100 x 45 x 75

Accessories

	Order No.	Description
■	8.756-481.0 ■	EASY!Force trigger gun (North American Model) - zero force required. Standard 1/4" connection for wand, 3/8" connection for hose.
■	9.802-225.0	3 - 5 GPM Chemical Injector Kit
■	8.754-990.0	12V Battery (required for hot water operation)
■	8.924-366.0	2-inch ball coupler
■	8.711-293.0	Zinc plated variable pressure lance

Options (factory installed)

	Order No.	Description
☐	8.924-367.0	Saddle Box (each)
☐	8.924-667.0	Lifting Kit
☐	8.924-370.0	LED Lights
☐	8.924-700.0	2-inch Collar Lock Coupler

Options (field installed)

	Order No.	Description
☐	8.750-682.0	Hose Reel Fixed 100', 5000 PSI, 325° F, equipped for 3/8" hose
☐	8.925-255.0	Hose Reel Bracket (Mount Kit)

■ Included ☐ Optional ■ Please note: NOT compatible with EASY!Lock.

For more information, contact Lorchem Technologies at:
(800) 788-8867 • info@lorchem.com • www.lorchem.com

TRK-2500 HDS 4.7/35

Convenient cleaning performance.

Kärcher's TRK-2500 HDS 4.7/35 pressure washer trailer package includes the TRK-200 trailer, HDS 4.7/35 Pe Cage pressure washer, mounting kit, battery and high and low-pressure hose reels. This package is rugged, affordable, versatile, and easy to ship and store.

The TRK-2500 is made of rugged 10-gauge steel. The wheel and axle assembly features leaf-spring suspension of up to 3,500 lbs. The 39-inch tongue features a swing-away hinge that saves on storage space.

Smart and reliable

- Electrical wiring recessed within tubular frame
- Lighted license plate holder and recessed tail lights
- 1,000 lb. swivel jack with a 2-inch ball coupler for quick and easy hook up of the trailer
- 3-way ball valve for easy switching of the water flow from the holding tank to a faucet
- High-density, polyethylene 200-gallon water tank with a 12-inch access port, 1 1/2-inch drain valve, 3/4-inch float valve and a 50-mesh inlet filter; and two 5/16-inch chains for additional safety
- Electric brakes and break away kit

Technical Data

Model	Part No.	Axle	(GVWR) lbs.	Water tank (gallons)	Ship weight (lbs)	Dimensions (L x W x H) inches
TRK-2500 HDS 4.7/35	1.103-843.0	Single	3500	200	1815	123 x 76 x 70

Options (field installed)

☐	8.917-558.0	Saddle Box (each)
☐	8.917-559.0	Rock Guard
☐	8.917-560.0	Utility Rack

■ Included ☐ Optional

TRK-2500 HDS 4.7/35 Package includes

Product	Description
TRK-2500	Single axle trailer, 3500 lbs GVWR, 200 gallon water tank
HDS 4.7/35 Pe Cage	Hot water pressure washer, 4.7 GPM, 3500 PSI, 688 CC, Honda GX630 engine, gas, 120V AC burner
Mounting Kit	Skid mounting kit
Battery	Battery installed on pressure washer
Hose reels	Factory installed high-pressure and low-pressure hose reels

HDS 4.7/35 Features

- Honda engine
- 1-1/4" full steel skid frame
- Burner available in 120V AC
- Kärcher belt-drive tri-plunger pump
- North American-style accessories
- Stainless steel coil wrap
- EASY!Force trigger gun with cruise control like technology uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use.
- Electric start engine.

Standard EASY!Force Accessory

Order No.	Description
8.756-481.0 ■	EASY!Force trigger gun (North American Model) - zero force required. Standard 1/4" connection for wand, 3/8" connection for hose.

■ Please note: NOT compatible with EASY!Lock.

For more information, contact Lorchem Technologies at:
(800) 788-8867 • info@lorchem.com • www.lorchem.com

TRK-2500

Shown with optional hot water pressure washer skid

High cleaning performance.

Kärcher's TRK-2500 pressure washer trailer is designed to accommodate a variety of pressure washer skids. This trailer package is rugged, affordable, versatile, and easy to ship and store.

The TRK-2500 is made of rugged 10-gauge steel. The wheel and axle assembly features leaf-spring suspension of up to 3,500 lbs. The 39-inch tongue features a swing-away hinge that saves on storage space.

Smart and reliable

- Electrical wiring recessed within tubular frame
- Lighted license plate holder and recessed tail lights
- 1,000 lb. swivel jack with a 2-inch ball coupler for quick and easy hook up of the trailer
- 3-way ball valve for easy switching of the water flow from the holding tank to a faucet
- High-density, polyethylene 200-gallon water tank with a 12-inch access port, 1 1/2-inch drain valve, 3/4-inch float valve and a 50-mesh inlet filter; and two 5/16-inch chains for additional safety
- Electric brakes and break away kit

Technical Data

Model	Part No.	Axle	(GVWR) lbs.	Water tank (gallons)	Ship weight (lbs)*
TRK-2500	1.103-819.0	Single	3500	200	1072

*trailer and water tank only

Options

	Order No.	Description
☐	8.917-294.0	North American Engineered Series Skid mounting kit (required for mounting pressure washer to trailer)

Options (factory installed)

	Order No.	Description
	8.917-558.0	Saddle Box (each)
	8.917-559.0	Rock Guard
	8.917-560.0	Utility Rack

Options (field installed)

	Order No.	Description
☐	8.917-398.0	Hydraulic Brakes
☐	8.917-554.0	High Pressure Hose Reel Kit
☐	8.924-493.0	2-5/16" Ball Hitch Coupler
☐	8.917-555.0	Low Pressure Hose Reel Kit
☐	8.917-556.0	Saddle Boxes (2)
☐	8.917-557.0	Rock Guard
☐	8.904-051.0	Battery Installed on Pressure Washer

■ Included ☐ Optional

For more information, contact Lorchem Technologies at:
(800) 788-8867 • info@lorchem.com • www.lorchem.com

TRK-6000, TRK-3500

TRK-6000 - shown with options and gas-powered hot water pressure washer; accommodates both gas and diesel-powered pressure washers. Tool box shown is no longer available on this unit.

TRK-3500 - shown with options; accommodates gasoline-powered pressure washers only.

Customizable mobile solution.

Kärcher has made customizing a mobile wash system for on-site cleaning as easy as 1-2-3:

1. Choose from 3 rugged trailers—the dual-axle TRK-6000 with 330-gallon water tank or the single-axle TRK-3500 or TRK-2500 with 200-gallon water tank.

2. Choose a compatible skid-mounted hot water pressure washer.

3. Customize your trailer with a broad selection of options and accessories, such as hose reels, chrome coverings, etc.

Smart and reliable

- Electrical wiring recessed within tubular frame
- Lighted license plate holder and recessed tail lights
- 1,000 lb. swivel jack with a 2-5/16-inch ball coupler for quick and easy hook up of the trailer.
- Two 3-way ball valve for easy switching of the water flow from the holding tank to a faucet
- Rugged steel cage for security while transporting.
- High-density, polyethylene 200-330 gallon water tank with a 12-inch access port, 1 1/2-inch drain valve, 3/4-inch float valve and a 50-mesh inlet filter; and two 5/16-inch chains for additional safety
- Electric brakes and break away kit

Technical Data

Model	Part No.	Axle	(GVWR) lbs.	Water tank (gallons)	Ship weight (lbs)
TRK-6000	1.103-807.0	Tandem	6000	330	1980
TRK-3500	1.103-806.0	Single	3500	200	840

*trailer and water tank only

Accessories

	Order No.	Description
☐	8.904-051.0	Battery installed on pressure washer
☐	8.902-436.0	3" Lunette eye hitch coupler (TRK-3500)
☐	8.902-438.0	Hydraulic brakes, two axles, 2-5/16" ball coupler (TRK-6000)
☐	8.902-441.0	Hydraulic brakes, single axle, 2" ball coupler (TRK-3500)
☐	8.902-452.0	Hydraulic brakes, two axles, 3" Lunette eye coupler (TRK-6000)
☐	8.924-493.0	From 2" to 2-5/16" ball hitch coupler (TRK-3500)
☐	8.902-471.0	3" Lunette eye hitch coupler (TRK-6000)
☐	8.902-442.0	Hydraulic Brakes Kit (Single axle, 3" Lunette eye hitch) (TRK-3500)
☐	8.912-409.0	2-5 gallon bucket chemical rack for TRK-6000 only (factory installed only)
☐	8.915-156.0	High-pressure hose, 3/8-inch x 100 ft., 2-Wire, installed
☐	8.902-447.0	Hose reel kit for 100 ft. Of 3/8-inch high-pressure hose
☐	8.902-448.0	Hose reel kit for 200 ft. Of 3/8-inch high-pressure hose
☐	8.902-449.0	Hose reel kit for 75 ft. Of 3/4-inch industrial garden hose
☐	8.902-455.0	Skid mounting & plumbing kit (required for mounting pressure washer to trailer)
☐	8.902-469.0	Sign plate
☐	8.902-466.0	Chrome wheels, pair, (2 pair required for TRK-6000)
☐	8.902-468.0	Chrome fenders, pair, TRK-6000 tandem axle
☐	8.902-467.0	Chrome fenders, pair, TRK-3500 single axle

■ Included ☐ Optional

For more information, contact Lorchem Technologies at:
(800) 788-8867 • info@lorchem.com • www.lorchem.com

PRO HD 400 ED

Practical anywhere.

The PRO HD 400 ED is a light weight, durable and compact cold water pressure washer that offers ultimate mobility for on-site applications and is designed to be stored, transported and operated in the vertical and horizontal position. It's features include a reliable 3-piston axial-pump with a brass cylinder head, an automatic pressure relief system for protecting the pump and storage options for accessories.

Mobility and durability

- Vertical and horizontal operation for maximum flexibility and stability.
- Rubber strap for secure storage of high-pressure hose.
- EASY!Force gun with cruise control like technology - uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use.

Technical data

Model	Part No.	GPM	PSI	Drive	Electrical	Amps	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
Pro HD 400 ED	1.520-990.0	1.7	1300	Direct	120V / 1ph ~ / 60 Hz	14	Kärcher Axial	45	36 x 14 x 13

Accessories

	Order No.	Description
■	4.118-005.0 ■	EASY!Force trigger gun
■	4.112-006.0 ■	33" Spray lance
■	6.110-034.0 ■	33' EASY!Lock hose
■	2.113-062.0 ■	Power nozzle, 030
□	4.113-003.0 ■	Rotating washing brush natural fiber bristles
□	4.111-022.0 ■	Nozzle connector
□	4.111-037.0 ■	Coupling
□	2.115-000.0 ■	Quick-release coupling
□	2.115-001.0 ■	Nipple
□	4.114-018.0 ■	Performance Dirtblaster
□	4.112-000.0 ■	41" Spray lance, 1050 mm
□	2.111-016.0 ■	Surface cleaner FR TR Classic
□	2.111-017.0 ■	Surface cleaner FR Classic DIY
□	4.111-032.0 ■	Adapter M 22 Swivel
□	4.112-011.0 ■	Screw connector part
□	6.110-034.0 ■	Extension hose 33'

■ Included □ Optional

■ Compatible with EASY!Lock

HD COMPACT CLASS

Designed to move.

The HD 1.8/13 C compact cold water pressure washer offers maximum portability, maneuverability and smart features. It can be stored, transported and operated in the vertical and horizontal position, and at 55.6 lbs, this professionally built unit can easily be moved by one person in and out of vehicles and around a cleaning site. It also includes storage options for accessories.

Mobility and easy maintenance

- Vertical and horizontal operation for maximum flexibility and stability.
- Additional carrying handle for easy loading and unloading, and moving
- Removable and easy to clean water inlet filter that protects the pump from debris.
- Rubber strap for secure storage of high-pressure hose.
- EASY!Force gun with cruise control like technology - uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use.

Technical data

Model	Part No.	GPM	PSI	Drive	Electrical	Amps	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HD 1.8/13 C	1.520-916.0	1.8	1300	Direct	120V / 1ph ~ / 60 Hz	14	Kärcher Axial	55.6	37 x 15 x 14

Accessories

	Order No.	Description
■	4.118-005.0 ■	EASY!Force trigger gun
■	4.112-006.0 ■	33" Spray lance
■	6.110-034.0 ■	33' EASY!Lock hose
■	4.117-027.0 ■	Triple jet nozzle, 032
□	2.112-000.0 ■	Inno Foam kit
□	2.112-010.0 ■	Gutter cleaning lance
□	4.112-035.0 ■	Flexible spray lance
□	6.110-049.0 ■	Pipe cleaning hose 65', 1740 psi
□	6.110-050.0 ■	Pipe cleaning hose 98', 1740 psi
□	6.110-008.0 ■	Pipe cleaning hose 65', 3625 psi
□	4.113-004.0 ■	Rotating washing brush nylon bristles
□	4.113-003.0 ■	Rotating washing brush natural fiber bristles
□	2.111-011.0 ■	Surface cleaner FR 30
□	2.111-016.0 ■	Surface cleaner FR TR Classic
□	2.111-010.0 ■	Surface cleaner FRV TR 30
□	4.115-006.0 ■	Wet blasting attachment
□	4.111-022.0 ■	Nozzle connector
□	4.111-037.0 ■	Coupling
□	2.115-000.0 ■	Quick-release coupling
□	2.115-001.0 ■	Nipple

■ Included □ Optional ■ Compatible with EASY!Lock

HD COMPACT CLASS

The compact class – fast and thorough.

These reliable, compact units offer the benefits of low weight, compact dimensions, easy handling and high cleaning performance. Ideal for workshops, courtyards, etc.

Smart features

- Telescopic push handle retracts for convenient, space-saving transport, such as in service vehicles or compact cars
- Automatic pressure cut-off when work is interrupted - saves on energy and water consumption
- EASY!Force gun with cruise control like technology - uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use.

Technical data

Model	Part No.	GPM	PSI	Drive	Electrical	Amps	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HD 2.3/15 C Ed	1.150-909.0	2.3	1500	Direct	120V / 1ph	20	Kärcher Axial	77	28 x 15 x 39
HD 3.0/20 C Ea	1.150-908.0	3	2000	Direct	240V / 1ph	20	Kärcher Axial	77	28 x 15 x 39

Accessories

	Order No.	Description
■	4.118-005.0 ■	EASY!Force trigger gun
■	4.112-006.0 ■	33" spray lance
■	6.110-034.0 ■	33' EASY!Lock hose
■	4.117-033.0 ■	Triple jet nozzle, 040 (for machine 1.150-909.0)
■	4.117-035.0 ■	Triple jet nozzle, 043 (for machine 1.150-908.0)
□	2.112-000.0 ■	Inno Foam kit
□	2.112-010.0 ■	Gutter cleaning lance
□	4.112-035.0 ■	Flexible spray lance
□	6.110-049.0 ■	Pipe cleaning hose 65', 1740 psi
□	6.110-050.0 ■	Pipe cleaning hose 98', 1740 psi
□	6.110-008.0 ■	Pipe cleaning hose 65', 3625 psi
□	4.113-004.0 ■	Rotating washing brush nylon bristles, for EASY!Lock
□	4.113-003.0 ■	Rotating washing brush natural fiber bristles, for EASY!Lock
□	2.111-011.0 ■	Surface cleaner FR 30
□	2.111-016.0 ■	FRV TR 30 hard surface cleaner
□	2.111-010.0 ■	Surface cleaner FRV TR 30
□	4.115-006.0 ■	Wet blasting attachment
□	2.111-009.0 ■	Nozzle kit
□	4.402-022.0 ■	Nozzle connector
□	4.111-037.0 ■	Coupling
□	2.115-000.0 ■	Quick-release coupling
□	2.115-001.0 ■	Nipple

■ Included □ Optional ■ Compatible with EASY!Lock

HD MID CLASS

Loaded with features.

This medium class machine is extremely mobile and user-friendly with low-speed four-pole single phase motor for continuous use.

Smart features

- Unique CHEM switch system allows operator to switch between two on-board detergent tanks without interruption; includes precise two-way metering valve to accurately vary detergent volume.
- Robust, three-piston axial pump feature detergent-resistant brass cylinder head and stainless valves; pump is protected by pressure switch and overflow valve.
- Features ground-fault circuit interrupter (GFCI) for operator safety

Technical data

Model	Part No.	GPM	PSI	Drive	HP	Electrical	Amps	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HD 3.0/20-4M Ea	1.524-905.0	1.3-3.0	435-2000	Direct	4.7	220-240V / 1ph	20	Kärcher Axial	105	44 x 18 x 20

Accessories

	Order No.	Description
■	4.118-005.0 ■	EASY!Force trigger gun
■	4.112-000.0 ■	33" spray lance
■	6.110-035.0 ■	33' EASY!Lock hose
■	2.113-009.0 ■	Triple jet nozzle, 040 (for machine 1.150-909.0)
■	4.118-007.0 ■	Triple jet nozzle, 043 (for machine 1.150-908.0)
□	2.112-000.0 ■	Inno Foam kit
□	2.112-010.0 ■	Gutter cleaning lance
□	2.111-013.0 ■	FR 30 ME surface cleaner
□	2.111-023.0 ■	FR TR 50 ME hard surface cleaner
□	2.111-011.0 ■	Surface cleaner FR 30
□	2.111-010.0 ■	FRV TR 30 hard surface cleaner
□	4.115-000.0 ■	Wet blasting attachment
□	4.115-006.0 ■	Wet blasting attachment
□	2.111-009.0 ■	Nozzle kit
□	2.113-003.0 ■	Power nozzle 40° spray angle

■ Included □ Optional ■ Compatible with EASY!Lock

HD SUPER CLASS

For tough jobs in non-stop use.

Where vast amounts of dirt accumulate every day, reliable Kärcher super class models provide indispensable services. Ideal for use in the construction, agricultural and forestry sectors as well as industrial and municipal facilities.

Smart features

- Robust, three-piston axial pumps features detergent-resistant brass cylinder head and stainless valves; pumps is protected by pressure switch and over flow valve.
- Low-speed, 4-pole, air-cooled motor runs quieter and cooler than conventional motors thus prolonging its service life
- EASY!Force gun with cruise control like technology - uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use.

Technical data

Model	Part No.	GPM	PSI	Drive	HP	Electrical	Amps	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HD 3.5/30-4S Ea	1.286-908.0	1.8-3.5	435-3000	Direct	9	220/240V / 1ph	28	Kärcher Axial	178	47 x 21 x 23
HD 4.5/32-4S Eb	1.286-909.0	2.2-4.5	435-3200	Direct	10	230V / 3ph	25	Kärcher Axial	178	47 x 21 x 23
HD 4.5/32-4S Ec	1.286-910.0	2.2-4.5	435-3200	Direct	10	460V / 3ph	14	Kärcher Axial	160	47 x 21 x 23

Accessories

	Order No.	Description
■	4.118-005.0 ■	EASY!Force trigger gun
■	4.112-000.0 ■	41" spray lance
■	6.110-030.0 ■	50' EASY!Lock hose with ANTI!Twist connection
■	2.113-022.0 ■	Power nozzle, 045 (for machine 1.286-908.0)
■	2.113-025.0 ■	Power nozzle, 055 (for machine 1.286-909.0)
■	4.118-008.0 ■	Servo control
☐	2.112-000.0 ■	Inno Foam kit
☐	2.112-015.0 ■	Gutter cleaning lance
☐	4.112-035.0 ■	Flexible spray lance
☐	6.110-049.0 ■	Pipe cleaning hose 65', 1740 psi
☐	6.110-050.0 ■	Pipe cleaning hose 98', 1740 psi
☐	6.110-008.0 ■	Pipe cleaning hose 65', 3625 psi
☐	2.111-023.0 ■	FR TR 50 ME hard surface cleaner
☐	2.111-012.0 ■	FRV TR 30 ME
☐	2.111-011.0 ■	Surface cleaner FR 30
☐	2.111-010.0 ■	FRV TR 30 hard surface cleaner
☐	4.115-000.0 ■	Wet blasting attachment
☐	2.113-020.0 ■	25° power nozzle for applying cleaning agent
☐	4.114-019.0 ■	Dirtblaster Nozzle 035
☐	4.637-033.0 ■	Detergent injector for high pressure
☐	4.111-037.0 ■	Coupling

■ Included ☐ Optional ■ Compatible with EASY!Lock

HD SPECIAL CLASS

For strict hygiene requirements.

Cold water high-pressure cleaner was designed specifically for all-purpose industrial use in the sanitary/food industry. This top-of-the-range machine from the compact class allows you to regulate pressure and water flow seamlessly.

High standard of hygiene

- Food-safe, non-marking high-pressure hose.
- Wear-resistant and non-marking gray wheels.
- Accepts inlet water at temperatures up to 180°F.
- Easy access to the variable pressure and water flow regulation and the "Inno Foam Set" high-pressure foam system can be used.
- EASY!Force gun with cruise control like technology - uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use.

Technical data

Model	Part No.	GPM	PSI	Drive	HP	Electrical	Amps	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HD 2.3/14 C Ed Food	1.150-912.0	2.3	1400	Direct	3.2	120V / 1ph	20	Kärcher Axial	78	39 x 15 x 28

Accessories

	Order No.	Description
■	4.118-015.0 ■	EASY!Force trigger gun for food applications
■	4.112-006.0 ■	33" spray lance
■	6.110-063.0 ■	50' EASY!Lock food grade hose with AVS hose reel connection
■	4.117-033.0 ■	Triple jet nozzle, 040
■	2.112-009.0 ■	Inno Foam (food grade)

■ Included ☐ Optional ■ Compatible with EASY!Lock

HD HAND HELD

Durable and dependable.

These industrial hand held units are significantly more rugged than typical consumer substitutes and are built with durable steel frames. Hand-held models come with a dependable axial pump, high pressure hose, a stainless steel lance and detergent injector with brass soap nozzle.

1 YEAR PUMP WARRANTY

Convenient and durable

- Durable steel frame
- Axial pump
- Portable, easy to transport

Technical data

Model	Part No.	GPM	PSI	Drive	HP	Electrical	Amps	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HD 2.0/10 Ed	1.575-400.0	2.0	1000	Direct	1.5	120V / 1ph	15	Comet Axial	85	24 x 19 x 22
HD 1.8/14 Ed	1.575-401.0	1.8	1400	Direct	2	120V / 1ph	20	Comet Axial	95	24 x 19 x 22

HD WALL MOUNTED

Shown with optional wall mount bracket part no. 8.920-952.0

Convenient and quiet.

Kärcher's wall-mount unit has a durable steel frame, uses a quiet 1725 RPM motor, and is perfect for in-shop uses. A remote on/off switch with a 10' electrical cord allows the machine to be mounted high on a wall away from backspray.

7 YEAR PUMP WARRANTY

Smart features and reliable

- Accepts hot water up to 180 degrees
- Remote on/off switch
- Kärcher Triplex crankcase pump

Technical data

Model	Part No.	GPM	PSI	Drive	HP	Electrical	Amps	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HD 2.0/14 Ed +	1.107-088.0	1.8	1400	Direct	2	120V / 1ph	20	Kärcher KE	123	20 x 19 x 17

Accessories

	Order No.	Description
☐	8.920-952.0	Wall mount bracket

■ Included ☐ Optional

For more information, contact Lorchem Technologies at:
(800) 788-8867 • info@lorchem.com • www.lorchem.com

HD SERIES ELECTRIC

Designed for versatility.

Kärcher's HD carts are corrosion-resistant aluminum pressure washers that easily convert from a cart to a skid for maximum cleaning versatility and durability. These reliable electric powered pressure washers have a low profile handle and compact footprint, making them easy to maneuver, and they offer a bypass loop for additional pump protection. 7-year pump warranty and flat-free tires.

Durable and smart

- Durable, corrosion resistant aluminum frame
- Modular design - weld free frame easily converts from cart to skid
- Flat free tires
- VRT3 Unloader with bypass loop - pump protection
- Commercial-duty Leuco crankcase pump

Technical Data

Model	Part No.	GPM	PSI	Drive	HP	Electrical	Amps	Pump	Pump RPM	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HD 2.0/1000 Ed	9.801-814.0	2.0	1000	Direct	1.5	120V / 1ph	15	Kärcher KF	1725	161	41 x 22 x 25
HD 1.9/1300 Ed	9.801-794.0	1.9	1300	Direct	2	120V / 1ph	20	Kärcher KF	1725	175	41 x 22 x 25
HD 3/1000 Ea	9.801-795.0	3.0	1000	Direct	2	120V / 1ph	20	Kärcher KF	1725	180	41 x 22 x 25
HD 3.5/2000 Ea	9.801-796.0	3.5	2000	Direct	5	230V / 1ph	22	Kärcher KF	3450	181	41 x 22 x 25

Accessories

	Order No.	Description
■	8.750-247.0	Gun
■	8.925-129.0	Hose
■	8.783-040.0	Lance
■	9.802-216.0	Chemical injector
■	8.712-398.0	Nozzle, QCEM-6540 Brass (Chem)
■	8.712-337.0	Nozzle, red, 035
■	8.712-338.0	Nozzle, yellow, 035
■	8.712-339.0	Nozzle, green, 035
■	8.712-340.0	Nozzle, white, 035
□	8.712-429.0	Rotary nozzle
□	8.925-229.0	Legacy, 100' x 3/8" ID, 6000 PSI, 2-wire, smooth cover, black high pressure hose
□	8.753-572.0	A+ Surface Cleaner SC21
□	8.753-573.0	A+ Surface Cleaner SC24
□	9.302-243.0	Legacy Turbo Nozzle, 4.0, 4350 PSI
□	8.710-620.0	Legacy Superlite stainless steel, 72" - 56.0 oz
□	9.807-754.0	Skid mount feet
□	9.807-750.0	37.5" long handle
□	9.807-753.0	Lance holder
□	9.807-752.0	Hose storage hook
□	9.807-751.0	Handle with hose reel

■ Included □ Optional

HD ROLL CAGE

Specialty applications.

These belt-drive, electric roll cage models feature cleaning power of 5000 PSI and are available with either 230/3 phase or 460/3 phase motors. These units are specialty machines perfect for use in the marine market cleaning the bottom of boats or in the concrete industry, mixers, forms and handling equipment. Both models are ETL safety certified.

Durable

- Rugged steel chassis & roll cage
- Kärcher Belt-drive crankcase pump
- Cleaning power of 5000 PSI
- Flat-free tires
- 20 HP motor
- 50' high-pressure hose

Technical data

Model	Part No.	GPM	PSI	Drive	HP	Electrical	Amps	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HD 5.0/50 Eb Cage	1.107-084.0	5.0	5000	Belt	20	230V / 3ph	48	Kärcher KX	524	42 x 26 x 30
HD 5.0/50 Ec Cage	1.107-087.0	5.0	5000	Belt	20	460V / 3ph	26	Kärcher KX	524	42 x 26 x 30

Options (field installed)

	Order No.	Description
☐	9.801-029.0	100' hose reel kit, 5000 PSI (hose not Included)

■ Included ☐ Optional

HD CABINET - BELT DRIVE

Industrial throughout.

Our cold-water cabinet units accept pre-heated water up to 180˚F. Protected in durable steel cabinets, they demonstrate industrial strength throughout, including belt-drive Kärcher crankcase pumps, industrial motors, and magnetic starters for operator safety.

ETL LISTED · 7 YEAR PUMP WARRANTY · EASY!Force

Wheel kit

- Wheel kit with detergent rack and optional hose reel.
- Floor stand with caster wheels.

Technical data

Model	Part No.	GPM	PSI	Drive	HP	Electrical	Amps	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HD 2.8/10 ST Ed B	1.575-300.0	2.8	1000	Belt	2	120V / 1ph	20	Kärcher KM	210	31 x 21 x 16
HD 4.2/20 ST Ea B	1.575-301.0	4.2	2000	Belt	6	230V / 1ph	29	Kärcher KM	285	31 x 21 x 16
HD 4.2/20 ST Eb B	1.575-302.0	4.2	2000	Belt	6	230V / 3ph	22	Kärcher KM	255	31 x 21 x 16
HD 4.2/20 ST Ec B	1.575-303.0	4.2	2000	Belt	6	460V / 3ph	11	Kärcher KM	260	31 x 21 x 16
HD 4.2/20 ST Eh B	1.575-305.0	4.2	2000	Belt	6	208V / 3ph	16	Kärcher KM	265	31 x 21 x 16
HD 3.5/30 ST Ea B	1.575-306.0	3.5	3000	Belt	7.5	230V / 1ph	36	Kärcher KM	330	31 x 21 x 16
HD 3.5/30 ST Eb B	1.575-307.0	3.5	3000	Belt	7.5	230V / 3ph	19	Kärcher KM	275	31 x 21 x 16
HD 3.5/30 ST Ec B	1.575-308.0	3.5	3000	Belt	7.5	460V / 3ph	11	Kärcher KM	270	31 x 21 x 16
HD 3.5/30 ST Eg B	1.575-309.0	3.5	3000	Belt	7.5	208V / 1ph	38	Kärcher KM	332	31 x 21 x 16
HD 3.5/30 ST Eh B	1.575-310.0	3.5	3000	Belt	7.5	208V / 3ph	23	Kärcher KM	271	31 x 21 x 16

Accessories

	Order No.	Description
■	8.756-481.0 ■	EASY!Force trigger gun (North American Model) - zero force required. Standard 1/4" connection for wand, 3/8" connection for hose.

Options (factory installed)

	Order No.	Description
☐	9.801-002.0	Conversion to Stainless Steel Cabinet
☐	9.801-011.0	Auto Start/Stop
☐	9.801-012.0	Time-Delay Shutdown
☐	9.801-013.0	Hour Meter

Options (field installed)

	Order No.	Description
☐	9.801-031.0	Wheel Kit with Detergent Rack
☐	9.801-033.0	Wall Mount Kit
☐	8.903-043.0	Stainless Steel Wall Mount Kit
☐	8.903-040.0	Floor Stand, 24" short
☐	9.801-034.0	Floor Stand, 36" Tall
☐	8.903-617.0	Stainless Steel Floor Stand, 36" Tall
☐	8.941-546.0	Stainless Steel Floor Stand, without Hose Hanger
☐	9.801-035.0	Caster Wheels for Floor Stand
☐	9.801-036.0*	Hose Reel Kit, Floor Stand Only, 100 ft, No Hose
☐	8.750-682.0*	100' x 3/8" fixed base hose reel
☐	8.919-437.0*	Wall Mount
☐	8.903-039.0*	Kit, Hose Reel w/Bracket for Stand & Wall Mount Kits

■ Included ☐ Optional ■ Please note: NOT compatible with EASY!Lock.

HD SERIES GAS

Easily converts from cart to skid.

Corrosion-resistant and light-weight, Kärcher's HD aluminum pressure washers can be utilized as a cart or a skid for maximum cleaning versatility and durability. These reliable Honda powered pressure washers offer a bypass loop for additional pump protection, 7-year pump warranty and flat-free tires.



Durable

- Reliable Honda GX engine
- Belt or direct drive models
- Durable VRT3 unloader with bypass loop diverts water flow when trigger gun is not activated.
- Aluminum frame - modular design - converts easily from cart to skid

Technical data

Model	Part No.	GPM	PSI	Drive	CC	Engine	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HD 3.0/27 G	9.807-719.0	3.0	2700	Direct	196	Honda GX200	Crankcase	112	45 x 28 x 29
HD 3.5/35 G	9.807-720.0	3.5	3500	Direct	270	Honda GX270	Crankcase	130	45 x 28 x 29
HD 4.0/40 G	9.807-721.0	4.0	4000	Direct	389	Honda GX390	Crankcase	149	45 x 28 x 29
HD 4.0/40 Ge*	9.807-722.0	4.0	4000	Direct	389	Honda GX390	Crankcase	158	45 x 28 x 29
HD 3.0/27 GB	9.807-723.0	3.0	2700	Belt	196	Honda GX200	Crankcase	123	45 x 28 x 29
HD 3.5/35 GB	9.807-724.0	3.5	3500	Belt	270	Honda GX270	Crankcase	156	45 x 28 x 29
HD 4.0/40 GB	9.807-725.0	4.0	4000	Belt	389	Honda GX390	Crankcase	160	45 x 28 x 29
HD 4.0/40 GeB*	9.807-726.0	4.0	4000	Belt	389	Honda GX390	Crankcase	196	45 x 28 x 29

*Electric start available on select models.

Accessories

	Order No.	Description
■	8.750-247.0	Trigger Gun, model M407
■	8.925-129.0	Hose, 50' x 3/8", 1w, TS, SOXSW
■	8.783-039.0	Lance 30" Zinc plated, handle & coupler (for HD 3.0/27 AG, HD 3.0/27 AGB)
■	8.783-040.0	Lance 44" Zinc plated, handle & coupler (for HD 3.4/35 G, HD 4.0/41 G, HD 4.0/41 Ge, HD 3.3/35 GB, HD 4.0/40 GB, HD 4.0/40 GeB)
■	9.802-216.0	Injector, Chem, NON ADJ, 0.083
☐	8.712-429.0	Nozzle
☐	8.925-229.0	Legacy, 100' x 3/8" ID, 6000 PSI, 2-wire, smooth cover, black high pressure hose
☐	8.753-572.0	A+ Surface Cleaner SC21
☐	8.753-573.0	A+ Surface Cleaner SC24
☐	9.302-243.0	Legacy Turbo Nozzle, 4.0, 4350 PSI
☐	8.710-620.0	Legacy Superlite stainless steel, 72" - 56.0 oz
☐	9.807-754.0	Skid mount feet
☐	9.807-750.0	37.5" long handle
☐	9.807-753.0	Lance holder
☐	9.807-752.0	Hose storage hook
☐	9.807-751.0	Handle with hose reel

■ Included ☐ Optional

For more information, contact Lorchem Technologies at:
(800) 788-8867 • info@lorchem.com • www.lorchem.com

HD SERIES GAS SKID

*Pressure washer sold separate.

Cleaning on the go.

The perfect accompaniment to Kärcher's HD Series Gas pressure washers – these mild steel skids offer two configurations:
1. Skid with a 50 gallon water tank and one 100' hose reel
or
2. Skid with two 100' hose reels.
The HD Series Gas skids fit within a standard UTV / ATV bed and work with three different direct drive aluminum pressure washers to offer ultimate portability and usability for various applications.

Durable

- 50 gallon water tank (HD Pallet Skid with Tank only)
- Forklift holes
- Includes skid feet
- 1 to 2, 100' hose reels
- Fits within standard UTV/ATV bed
- Assembly required

Technical data

Model	Part No.	Frame Material	Description	Compatible Pressure Washer (sold separately)	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HD Pallet Skid with Tank	9.807-833.0	Mild Steel	50 gal water tank and 1 hose reel	HD 3.0/27 G 9.807-719.0 HD 3.4/35 G 9.807-720.0 HD 4.0/40 G 9.807-721.0	185	40 x 48 x 35
HD Pallet Skid with 2 Hose Reels	9.807-838.0	Mild Steel	2 hose reels	HD 3.0/27 G 9.807-719.0 HD 3.4/35 G 9.807-720.0 HD 4.0/40 G 9.807-721.0	172	47 x 40 x 35

Options (field installed)

	Order No.	Description
☐	8.923-105.0	Rubber feet kit
☐	8.923-107.0	Inlet filter kit
☐	8.923-106.0	Lifting eye bolts kit
☐	8.923-108.0	Three-way valve kit

■ Included ☐ Optional

HD CART

Compact and dependable.

The HD Carts are tough gasoline-powered direct-drive cold water machines that deliver cleaning power of up to 4000 PSI. Built on compact sturdy steel frames, each unit features a dependable industrial-grade Honda engine, Kärcher crankcase pump, hose/gun rack, detergent injection, and tubed pneumatic tires.

Durable and reliable design

- Steel frame with powder coat finish
- Commercial grade Honda GX engine
- Cleaning power up to 4000 PSI
- Industrial direct-drive Kärcher crankcase pump

Technical data

Model	Part No.	GPM	PSI	Drive	CC	Engine	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HD 2.3/24 P	1.575-100.0	2.3	2400	Direct	163	Honda GX160	Kärcher KP	130	35 x 21 x 24
HD 2.5/27 P	1.575-101.0	2.5	2700	Direct	196	Honda GX200	Kärcher KP	135	35 x 21 x 24
HD 3.0/30 P	1.575-102.0	3.0	3000	Direct	270	Honda GX270	Kärcher KP	175	35 x 21 x 24
HD 3.8/35 P	1.575-104.0	3.8	3500	Direct	389	Honda GX390	Kärcher KS	185	35 x 21 x 24
HD 3.5/40 P	1.107-223.0	3.5	4000	Direct	389	Honda GX390	Kärcher KS	188	35 x 21 x 24

Options (field installed)

	Order No.	Description
☐	9.801-026.0	100' EZEE Hose Reel kit (hose not Included)

■ Included ☐ Optional

HD PB CART

Reliable and professional.

Our cold-water series provides a broad selection of rugged belt-drive units, all with reliable Honda GX engines, which deliver cleaning volume of up to 3.7 GPM. Each model is ETL certified to UL safety standards and comes with a rugged steel chassis, cast iron belt pulley system, flat-free tires, and industrial-grade Kärcher crankcase pump.

ETL LISTED · 7 YEAR PUMP WARRANTY · FLAT FREE TIRES · POWERED by HONDA

Durable and reliable design

- Powder coated steel chassis
- Reliable Honda GX engine
- Onboard hose and lance storage
- Water volume up to 3.7 GPM
- Industrial belt-drive Kärcher pump
- Flat-free tires
- Quick connect nozzles

Technical data

Model	Part No.	GPM	PSI	Drive	CC	Engine	Fuel	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HD 3.0/30 PB	1.575-152.0	3.0	3000	Belt	270	Honda GX270	Gas	Kärcher KB	225	45 x 26 x 24
HD 3.7/35 PB	1.575-154.0	3.7	3500	Belt	389	Honda GX390	Gas	Kärcher KM	250	45 x 26 x 24
HD 3.0/40 PB	1.575-155.0	3.0	4000	Belt	389	Honda GX390	Gas	Kärcher KM	250	45 x 26 x 24

HD PB/DB CAGE

Extra rugged and powerful.

Our roll cage models are the most powerful units in our cold water line, with cleaning power of up to 5000 PSI. Protected by a rugged powder coated roll cage built of 1-1/4" steel, the PB Cage units feature powerful Vanguard or Honda engines, tri-plunger oil bath Kärcher pumps, flat-free tires, and an extra rugged belt-drive assembly with notched V belts and cast iron pulleys.

ETL LISTED · 7 YEAR PUMP WARRANTY · POWERED by HONDA

Durable and reliable design

- Belt-drive
- Rugged steel chassis & roll cage
- Honda or Vanguard engine
- Cleaning power up to 5000 PSI
- Electric start on dual-axle models*
- Industrial belt-drive Kärcher pump with 7-year warranty
- Flat-free tires

Technical data

Model	Part No.	GPM	PSI	Drive	CC	Engine	Fuel	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
HD 3.7/35 PB Cage	1.575-205.0	3.7	3500	Belt	389	Honda GX390	Gas	Kärcher KM	350	42 x 26 x 30
HD 4.0/40 PB Cage	1.575-207.0	4.0	4000	Belt	479	Vanguard 16	Gas	Kärcher KT	470	42 x 26 x 30
HD 4.0/50 PeB Cage*	1.575-200.0	4.0	5000	Belt	688	Honda GX630	Gas	Kärcher KX	495	42 x 26 x 30
HD 4.5/50 PeB Cage*	1.575-201.0	4.5	5000	Belt	688	Honda GX660	Gas	Kärcher KX	500	42 x 26 x 30

Options (field installed)

	Order No.	Description
☐	9.801-028.0	100' EZEE Hose Reel kit, single axle (hose not Included)
☐	9.801-029.0	100' Hose Reel kit, 5000 psi, double axle (hose not Included)

■ Included ☐ Optional

HD HAND HELD

Rugged and dependable.

This industrial hand held unit is significantly more rugged than typical consumer substitutes and is built with durable steel frames. Hand-held model comes with a dependable axial pump, high pressure hose, a stainless steel lance and detergent injector with brass soap nozzle.

Durable and reliable design

- Durable steel frame
- Axial pump
- Portable
- Detergent injector

Technical data

Model	Part No.	GPM	PSI	Drive	HP	CC	Engine	Pump	Weight (lbs)	Dimensions (L x W x H) inches
HD 2.3/24 P	1.575-350.0	2.3	2400	Direct	5.5	160	Honda GX160	Kärcher Axial	163	16 x 24 x 22

HDS HEATER

Hot Water Heater.

For attaching to a cold water pressure washer

Our Kärcher Series water heater provides supplemental heat to cold water machines, giving users the benefits of hot water cleaning when it's needed. An electric-powered diesel heated unit, the Heater 5.0/30 Ed effectively heats water at a rate of up to 5 gallons per minute.

Durable and reliable design

- Effective heating of up to 5 GPM
- Heavy-duty, steel cabinet protected by an epoxy powder coat finish
- Portable

Technical data

Model	Part No.	GPM	PSI	Electrical	Amps	Heated by	Ship Weight (lbs)	Ship Dimensions (L x W x H) inches
Heater 5.0/30 Ed	1.575-650.0	to 5	up to 3000	120V / 1ph	5	Diesel	330	35 x 47 x 50