

Mobile High-Pressure Cleaning Systems Mounted on Trailers



Mix-and-Match Pressure Washers with Optional Accessories to Create a Mobile Wash System Ideal for On-Site Cleaning

Kärcher has made customizing a trailer-mounted wash system for on-site cleaning as easy as 1-2-3.

• **Step 1:** Choose from two rugged trailers—the dual-axle TRK-6000 or the single-axle TRK-3500.

• **Step 2:** Select from

9 models of the skid-mounted Shark Series hot water pressure washers.

• **Step 3:** Customize your trailer with a broad selection of options and accessories, such as hose reels, chrome coverings, work lamp, etc.

Both trailers are made of extra-rugged 2-by-3 inch structural tubing. The wheel and axle assembly feature leaf-spring suspension of up to 3,500 lbs. per axle and 15-inch, white-spoke wheels. A powder-coated epoxy finish gives the package added weather protection.

- Tandem or Single Axle Trailers
- Fit With Any of 9 Hot Water Pressure Washers**
- 330 or 200 Gallon Water Tank
- Electrical Wiring Recessed Within Tubular Frame
- Many Accessories Available

TYPICAL APPLICATIONS

- On-Site Cleaning
- Heavy Equipment
- Truck Fleets
- Facilities
- Docks, Floors
- Trailers
- Transports
- Machinery

WHY KÄRCHER



Kärcher is the most trusted name in pressure washers—a fact confirmed when Kärcher was the only brand

selected to clean the famous Mount Rushmore National Monument in 2005.

Founder Alfred Kärcher invented hot water pressure washing in 1950. Today, as the world's largest manufacturer of pressure washers, Kärcher is the recognized innovative leader in the industry with over 300 patents.



TRK-6000 Dimensions:
178"L x 80"W x 62"H



TRK-3500 Dimensions:
130"L x 73"W x 58"H

- Extra-rugged 2-by-3 inch **structural tubing** is covered with a powder-coated epoxy black finish for all-weather protection
- Electrical **wiring** is recessed within the tubular frame
- Lighted **license plate holder** and recessed tail lights
- 1,500 lb.-rated **swivel jack** with a 2⁵/₁₆-inch ball coupler for quick and easy hook up of the trailer
- Two 3-way **ball valves** for easy switching of the water flow from the holding tank to a faucet
- Durable **steel cage** for holding the tank and pressure washer in place
- High-density, polyethylene **water tank** with 12-inch access port, 1/2-inch drain valve, 3/4-inch float valve and a 50-mesh inlet filter; two 5/16-inch chains for additional safety

- **Wheel and axle assembly** has an industrial undercarriage leaf-spring suspension of up to 3,500 lbs. per axle and 15-inch, white-spoke wheels (TRK-6000 above shown with optional chrome wheels and fenders)

Options and upgrades include:

- A broad selection of brakes
- Hose reel and mounting kits
- Lunette eye coupler
- Chrome wheel and fender upgrade
- Fuel tank, tool box, chemical rack

Model and Order No.	Axle	Load Capacity	Water Tank	Ship Wt*
TRK-3500	Single	3300 lbs	200 gallons	840 lbs
TRK-6000	Tandem	6000 lbs	330 gallons	1980 lbs

*Trailer only; does not include skid-mounted pressure washer
** Diesel engine skids require TRK-6000 trailer



1150 Davis Road, Suite J, Elgin, IL 60123
P: (847) 468-8800 • (800) 788-8867 • F: (847) 468-8811
www.lorchem.com • info@lorchem.com

We Know How To Get Things **CLEAN**