# LANDA®

Pressure Washer Equipment | Detergents | Parts & Accessories















1150 Davis Road, Suite J • Elgin, IL 60123 (800) 788-8867 • info@lorchem.com • www.lorchem.com

We Know How To Get Things CLEAN

#### Landa Water Jet Surface Cleaner

Water Jet is the ultimate industrial surface cleaner on the market.

It handles easier, cleans faster and holds up better under the toughest conditions.

The Water Jet's spray bar spins at 2,000 RPM and can be adjusted to blast concrete but not dig up asphalt or wood. The rotating bar and shaft are made of stainless steel with sealed precision guide bearings for low maintenance and a long life.

A holster-mounted trigger gun and insulated wand make for convenient spot cleaning in hard-to-reach places.

Other features include:

· Made of durable, rust-free polyethylene, for easy handling, but weighs only 45 lbs

· Pneumatic tires on steel wheels make for easy maneuvering on all surfaces

- Easy-to-clean, in-line filter keeps spray nozzles from plugging
- · Auto switching between surface cleaner and holster-mounted wand
- · Tri-lingual warnings and operating instructions
- · Collapsible handle for ease in transporting







# LANDA

Fatigue-Free Trigger Handle: Turns the unit off and on for

operator safety.

Tangle-Free Hose: Swivel connection keeps hose from tangling while operating.

> Holster-Mounted Gun: Keeps trigger gun close by for quick spot cleaning of hard-to-reach places.

> > **Variable Height Adjustment:** Allows you to raise or lower the spray bar so you can blast off concrete, but not dig up softer surfaces.

> > > **Corrosion-Free:** Rotating bar and shaft are made of stainless steel with sealed precision guide bearing for low maintenance and long life; backed by 1-year warranty.

Easy to Handle: Swivel caster wheel, sealed for added protection against debris, makes for easy maneuvering into corners and tight spaces.

· Rating: Super-duty

seat for longer life.

8.707-011.0

**Rotary Union** 

· Recommended Usage: Heavy

**Built to Last:** Self-lubricating rotary union is protected in

a stainless steel housing and

features industrial strength ball

bearings and tungsten carbide

- Attaches to: Any hot or cold water pressure washer with minimum of 2,000 PSI, 190°F
- Max PSI: 4,000
- Max Temp: 200°F
- Cleaning Width: 20"

# **Landa Cyclone Surface Cleaner**

The economy model flat surface cleaner, Landa's Cyclone is the price-competitive surface cleaner with many of the same design features that have made the top-of-the-line Water Jet so popular.

The Cyclone's non-adjustable spray bar also spins at 2,000 RPM and seemingly glides across flat surfaces riding on the evenly balanced tubed pneumatic tires and swivel caster wheel.

The rotating bar is made of stainless steel with medium-duty sealed precision guide bearings.

#### Other features include:

- · Durable, rust-free polyethylene spray housing
- Fatigue-free trigger handle turns unit on/off for operator safety
- Tangle-free hose connection for ease of maneuvering
- Tri-lingual operating instructions for added liability protection



# **Whisper Wash Flat Surface Cleaners**



- Saves labor, fuel & water
- · Eliminates overspray and zebra striping
- · Use with conventional pressure washers
- · Use with cold or hot water
- Balanced spray bar
- 2,000 to 4,000 PSI
- 2,500 RPM

#### **Applications:**

- · Service Stations
- Pool & Patio Decks
- Warehouse Floors
- Loading Docks
- · Parking Lots
- · Public Facilities
- Restaurants
- Gondolas
- Stadiums
- Marina Docks

- Quick connection

#### Driveways

- Sidewalks
- School Yards
- And lots more!

#### "Maxima 36" Flat Surface Cleaner



- · Portable Breakaway Handle
- 212°F
- 4-10 GPM
- 2.500 RPM
- Dimensions: Cover: 36" Handle: 77"
- · Weight 37 lbs



Part #	Old No.	Description
8.710-089.0	343636	Maxima 36

# "Big Guy" Flat Surface Cleaner



- · Powder-coated aluminum housing
- Oversized, self-lubricating twin thrust bearings
- · Choice of 2 or 4 nozzles
- 10" pneumatic tires, 4" caster
- Crafted with durable stainless steel & aircraft aluminum
- 212°F
- 4-10 GPM
- Dimensions: 28" x 44" x 12"
- · Weight 48 lbs



Part #	Old No.	Description
8.710-074.0	343606	Whisper Wash Big Guy 2 Nozzles
8.710-075.0	343607	Whisper Wash Big Guy 4 Nozzles
8.750-604.0		Complete Swivel Kit, New Style;
		Classic, Big Guy & Ground Force
8.701-879.0	092105	Repair Kit, Seal, Big Guy & Classic
8.701-874.0	092101	Spraybar, 4 Nozzle, Big Guy
8.701-876.0	092102	Spraybar, 2 Nozzle, Big Guy

#### "Ground Force" Flat Surface Cleaner



- · Flip and fold handle
- · Choice of 2 or 4 nozzles
- · Rebuildable swivel
- 212°F
- 4-10 GPM
- Dimensions: 24" x 60" x 9"
- · Weight 29 lbs

Part #	Old No.	Description
8.710-076.0	343608	Ground Force

#### "The Classic" Flat Surface Cleaner





- · Portable breakaway handle
- · ABS Housing
- · 2" nylon brush
- 212°F
- 4-10 GPM
- Dimensions: 19" x 77" x 12"
- · Weight 28 lbs

Part #	Old No.	Description	
8.710-073.0	343605	Whisper Wash Classic	
8.750-604.0	<b>8.750-604.0</b> Complete Swivel Kit, New Style;		
		Classic, Big Guy & Ground Force	
8.701-879.0	092105	Repair Kit, Seal, Big Guy & Classic	

# "Ultra Clean HC" **Flat Surface Cleaner**



- · 2" nylon brush
- · Powder-coated handle
- 185°F
- 3-6 GPM
- Dimensions: 16" x 43" x 9"
- · Weight 19 lbs





Γαιι π	Olu No.	Description		
8.710-071.0	343603	Whisper Wash Ultra Clean HC		
Repair Kits				
Part #	Old No.	Description		
8.701-879.0	092105	Seal Kit; Classic, Big Guy & Ground Force		
8.701-882.0	092108	Seal Kit; Ultra Clean		
8.701-883.0	092109	Complete Swivel Kit; Ultra Clean		
8.750-604.0		Complete Swivel Kit, New Style;		
		Classic, Big Guy & Ground Force		
8.707-653.0	251119	2.5 x 25° 1/4" nozzle fits All Models		
		·		



#### "Ultra Clean WW" Surface Cleaner

- ABS Housing
- · Four 3" casters
- · Powder-coated handle
- 185°F
- 3-6 GPM
- 2,500 RPM
- Dimensions: 19" x 43" x 9"
- · Weight 23 lbs



Part #	Old No.	Description
8.710-072.0	343604	Whisper Wash Ultra Clean WW

#### Mosmatic Surface Cleaners 700 1111



Specially designed recovery system allows operators to collect the water and dirt from the cleaning area with the help of a vacuum unit.



Part #	Description	List Price
8.751-299.0	Surface Cleaner w/ recovery, 21" SS deck,	
	2 arms / 2 nozzles, 1 HP-gun	
8.751-300.0	Surface Cleaner w/ recovery, 21" SS deck,	
	2 arms / 2 nozzles, 2 HP-gun	
	(gum remover nozzle sold separately)	
8.751-301.0	Gum Remover Nozzle (for 8.751-300.0)	

#### **Mosmatic Gun Swivel**



Mounts to your high pressure gun or lance for an easy turning, low maintenance gun swivel.



- 4,000 PSI
- 250°F
- 30 RPM

Part #	Old No.	Description
8.712-467.0	421057	1/4" MPT / 1/4" FPT Gun Swivel
8.712-466.0	421056	3/8" MPT / 3/8" FPT Gun Swivel

# Mosmatic Surface Cleaners & Duct Cleaner

#### **Turbo Surface Cleaner**

Delivers high-pressure performance with low maintenance for any hot or cold pressure washer. Completely stainless steel design makes this the toughest surface cleaner available in the pressure cleaning market.



Swiss engineered with high RPM Swivel features reinforced self-lubricated stainless steel ball bearings and dual spring based carbide seal bushings for long-lasting operation under tuff conditions.

Ideal for Pressure Washer Contractor to clean Walls, Ceilings, Public Facilities, Tile Floors and other hard to reach areas. Uses 1/8" meg 1503 nozzles.

#### **Duct Cleaner**

Designed as an accessory for use with high pressure pumps or pressure washers. Cleans Ducts, Chutes, Vents, Restaurant Exhausts, Tanks, etc.

Self rotating and feeding stainless steel triple bearing system for constant easy turning. Nozzle holders are 1/8" NPTF. Nozzles are sold separately.



- 250°F4,000 PSI
- 2lbs
- Inlet Ports: 3/8" NPTF



#### 12" Surface Cleaner

Designed for effortless cleaning of small areas including walls and angled surfaces. High RPM swivel with integrated toggle joint and adjustable tension system.

- 250°F
- 4,000 PSI
- 9lbs
- 12" SS Cover



Part #	Old No.	Description	PSI
8.712-284.0	411171A	Turbo Cleaner - 8"	4000
8.712-285.0	411172	Toggle Joint KGK	4000
8.712-280.0	411156	Duct Cleaner TXR-2s, Adjustable	4000
8.712-279.0	411155	Duct Cleaner TXR-2s, Fixed	4000
8.749-911.0		Surface Cleaner - 12"	4000


#### **Mosmatic Roof Cleaner**



Industrial-quality tool specially designed for efficient, high pressure roof cleaing while keeping the operator in a safe area.



- 4,000 PSI
- 250°F
- 31.9 lbs.
- · Pressure gauge
- · Ball valve
- Adjustable wheels (height & width)
- Safety eye connection for rope or cable
- (2) 1/8" nozzles sold separately





# **Undercarriage Cleaner**



No more crawling under a vehicle

Simply connect to your hot or cold water pressure washer

· Easy to handle & maneuver

· Removes road grime, fuel & oil contaminants

• Removes snow sludge & ice

· Provides a clean working environment for technicians

Stainless steel rotating assembly built to withstand pressures up to 4,000 PSI and 250°F

• 5.5" Required Clearance

• 7,250 PSI Carbon Steel Ball Valve

• 4 Nozzles: (2) 0° #2.0, (2) 25° #2.0



Part #	Description
8.749-303.0	Undercarriage Cleaner

# **Vinyl Skid Covers**

**LANDA**°

Custom-designed covers provide all-weather protection for Landa's skid-mounted pressure washers.

Made of seamless, truck-tarp-quality, vinyl-coated polyester (18 oz. per square yard), the covers fit snugly over the equipment so there is no need to tie down the cover.

The covers are both waterproof and capable of withstanding high winds.



Part #	Old No.	Description		
8.709-109.0	2-9025	SDHW, SGHW, Vinyl Cover		
8.749-946.0		PGHW, PGDC, Vinyl Cover		
8.709-111.0	<b>.709-111.0 2-9026</b> PGHW, PGDC (pre-2008 models only)			

#### **Goff's Curtain Walls**

Build a Power Wash Cell to meet your needs. Goff's Curtain Walls™ increase useable floor space while controlling overspray, contaminants, climate, and noise levels. Curtain Walls™ glide easily on steel track and dual-wheeled roll-erhooks. Made from a combination of 14-oz. heavy-duty, reinforced vinyl and double-polished 20-mil clear PVC material. Reinforced hems and chain-weighted lower hems add durability. Hook and loop fasteners on side hems attach to adjacent panels. Meet NFPA-701 requirements for flame retardancy. Curtains are also rot and mildew resistant. Standard model has a white vinyl top, clear PVC center, and blue vinyl bottom.










- #2 Brass tooth grommets on 1' centers
- 14 oz. reinforced vinyl white top section
- · All seams double locked stitched
- Hook & Loop Fasteners allow adjacent panels to be easily attached to one another
- · 20 mil. double polished clear window
- All sections joined together using mildew/ rot resistant thread
- 14 oz. reinforced colored vinyl section (your choice of over 12 different colors)
- · Chain weighted lower hem









Part #	Old No.	Description	PSI	
Single				
9.841-694.0	681133	6' width x 12' high	1500	
8.717-007.0	681083	12' width x 8' high	1500	
8.717-008.0	681084	12' width x 9' high	1500	
8.739-485.0	681082	12' width x 12' high	1500	
8.717-009.0	681086	24' width x 10' high	1500	
8.739-486.0	681087	24' width x 12' high	1500	
Station				
9.841-695.0	681145	4-sided x 12' high	1500	

#### Other sizes available - call for details

Includes hardware, track & rollers (white top, clear center & blue bottom panel). All 2,3 & 4-sided stations are 12' wide x 24' long (see diagram above).

#### **Water Broom 16**"





- 4,000 PSI
- Fits any 1/4" wand
- Requires (4) 1/4" nozzles and wand

Part #	Old No.	Description
8.710-082.0	343615	Water Broom 16"

#### **Landa Industrial Sandblasters**

**LANDA**°

For the extra-tough cleaning jobs, wet-sandblasting is the dust-free solution.

Landa's sandblasters attach to a hot or cold water pressure washer and, using a venturi, mixes sand or other abrasive media with the high-pressure spray to create enough cleaning power to strip paint off concrete and barnacles from a ship's hull.

The sandblasting nozzle is made of tungsten carbide for long life. There are two models—a top-of-the-line steel pot (photo at right) with tight-fitting lid or with a probe only.

# Other features include: · Quick-connect coupler for ease in attaching sand probe or pot

- · Valve for metering the flow of the media
- Tubed, pneumatic tires for easy maneuvering





- Recommended Usage: Heavy
- Attaches to: Any hot or cold water pressure washer with minimum volume of 4 GPM







MINDBLASTER FOR PRESSURE WAS

Part #	Old No.	Description
8.904-470.0	4-011201	Sandblaster w/ Pot (Carbide)
8.904-472.0	4-011211	Sandblaster w/ Probe (Carbide)

#### **Sandblast Hose**

# **LANDA**°

Heavy-duty spiralite hose available preassembled or by the foot.



- 3/4" spiralite sand hose with air hose locking couplers
- -30°F to 130°F

Part #	Old No.	Size: ID	Temp	Description
8.711-809.0	4-02190000	3/4"	130°F	Sand, Spiralite /ft
8.711-839.0	4-02199925	3/4" x 25'	130°F	Assy, Sand, Spiralite 25'
8.711-840.0	4-02199940	3/4" x 40'	130°F	Assy, Sand, Spiralite 40'
8.711-811.0		1"	130°F	Sand, Spiralite /ft

#### **Landa Sand Nozzle**

LANDA

Tungsten Carbide provides maximum durability for sand blasting application.



- · Carbide insert
- · Light weight
- · Easily changed

Part #	Old No.	Description	
8.712-416.0	4-2002	Carbide Sand Nozzle	



#### **Professional Sandblast Head**




- Long-wearing carbide sand nozzle
- 1/4" FPT water inlet
- 200°F
- 10 GPM
- 3,500 PSI
- Sand probe weight 6 oz, length 16"
- · Head weight 13 oz

Part #	Old No.	Nozzle Size
8.711-242.0	391631	3.5
8.711-243.0	391632	4.0
8.711-244.0	391633	4.5
8.904-403.0	391634	5.0
8.711-245.0	391635	5.5
8.904-404.0	391636	6.0
8.711-246.0	391637	8.0

Part #	Old No.	Description
8.711-247.0	391640	Sand Probe
8.901-264.0	121041	1/2" ID Polybraid Tubing, 25'

## Sandblast Kit Carbide Nozzle Industrial Grade





- 5,500 PSI max working pressure
- 10 GPM max flow
- 200°F
- 10 lbs.
- Nozzle tips sold separately

Part #	Old No.	Description
8.701-485.0	084079	Sand Blast Kit DWSDBTK

# **Sandblast Nozzles Tips**



Replacement tips for Sandblaster Kit (Part # 8.701-485.0 - Old No. 084079)

• Use 1/4" meg 5<sup>=</sup> spray tip

Part #	Old No.	Description
8.707-668.0	251159	4.0 x 5° Tip
8.707-685.0	251198	5.0 x 5° Tip
8.707-696.0	251221	5.5 x 5° Tip
8.707-701.0	251237	6.0 x 5° Tip
8.707-709.0	251256	6.5 x 5° Tip

# Sandblast Kit Carbide Nozzle Industrial Grade



A Venturi orifice creates a uniform blast pattern, doubles sand velocity and produces up to 45% more work with 20% less sand.

Kit contents: Sand head with carbide nozzle, 20" lance, sand probe, 13-1/2' sand hose, sand flow regulator valve



8.701-617.0

- · Solid carbide blast nozzle
- · Venturi orifice design
- · Volume control sand feed valve
- Up to 3,500 PSI
- Up to 750 lbs of sand per hour

Part #	Old No.	Orifice Size
8.904-397.0	391554X	4.0
8.904-396.0	391553X	4.5
8.904-398.0	391555X	5.0
8.904-395.0	391550X	5.5
8.904-399.0	391556X	6.0
8.904-400.0	391557X	7.0
8.904-402.0	391560X	10.0

Part #	Old No.	Description
8.701-620.0	086941	Solid Carbide Nozzle only
8.701-617.0	086930	Probe only

# **Tip-Jet Nozzles** for water nozzle replacement or system volume changes.

Part #	Old No.	Orifice Size
8.708-016.0	253316	3.0
8.708-019.0	253330	4.0
8.708-023.0	253338	4.5
8.708-027.0	253346	5.0
8.708-031.0	253355	5.5
8.708-035.0	253365	6.0
8.708-039.0	253375	6.5
8.708-042.0	253383	7.0
8.708-046.0	253392	7.5
8.708-050.0	253400	8.0
8.708-054.0	253415	9.0
8.708-058.0	253456	10.0

### **Dual Chemical Systems**



- New deep-ribbed yellow casing, stays flexible even in cold temperature
- Hose assembly complete with gun and amphenol connectors pre-wired
- Fully compatible with Power Blaster, Two-Step, Chemex and most other cold water dual chemical systems

Part #	Old No.	Description
Complete Hose	Assembly	
8.709-044.0	285116	80' R2 Electric (5 wire)
8.709-045.0	285120	100' R2 Electric (5 wire)
Lance Attachme	nt Parts	
8.709-049.0	285136	Female Receiver
8.709-050.0	285137	Male Lance Swivel
8.709-051.0	285138	Retainer Nut
Complete Remo	te Gun Unit	
8.709-046.0	285125	Gun, Electric
Remote Gun/Hos	se Parts	
8.709-048.0	285135	Gun Housing
8.709-053.0	285139	Switch P/B
8.709-054.0	285140	Switch, Chemical
8.709-056.0	285142	Switch Plate
8.903-083.0	285144	O-ring, Nipple (2 req'd)
8.903-084.0	285145	O-ring, Nipple (Bags of 50)
8.709-060.0	285175	Swivel Adapter
8.709-061.0	285177	Cord Grip
8.709-063.0	285181	Oetiker clamp
8.709-064.0	285187	Switch – Push Button Trigger
8.709-065.0	285189	Toggle, DPDT (Trig) On/Off/On

#### **Stainless Steel Sewer Nozzles**



- 4,100 PSI
- · Corrosion resistant stainless steel
- One forward orifice
- · Three rear orifices

Part #	Old No.	FPT	Size	
8.710-905.0	373075	1/8"	5.0	
8.710-906.0	373076	1/8"	5.5	
8.710-907.0	373077	1/8"	6.0	
8.710-908.0	373078	1/4"	6.5	
8.710-909.0	373079	1/4"	7.0	
8.710-910.0	373080	1/4"	9.5	

## **Sewer/Tube Cleaning Nozzles**



The reverse jets on the fixed and rotary nozzles pull the hose through the tube or sewer line and blast debris from line or tube walls.



- Backward ports drive the nozzle forward and flush debris
- · Forward ports blast into pipe and breaks up clogs & debris
- · Physically small for cornering ability
- 4,200 PSI
- · Corrosion resistant stainless steel construction
- · Orifice size indicated on non-rotating styles
- · Rotating style adds extra agitation and surface cleaning

Part #	Old No.	Nozzle	Orifice Size	0.D.	Ports
Non-Rotating Se	wer Nozzle	s			
8.710-875.0	373024	1/8"	4.5	.580"	0-forward, 3 back
8.710-874.0	373023	1/8"	5.5	.580"	1-forward, 3 back
8.710-878.0	373027	1/4"	4.5	.730"	1-forward, 3 back
8.710-876.0	373025	1/4"	5.5	.730"	1-forward, 3 back
8.710-877.0	373026	1/4"	6.0	.730"	1-forward, 4 back
8.710-880.0	373029	1/4"	7.5	.730"	1-forward, 4 back
8.710-879.0	373028	1/4"	8.0	.730"	1-forward, 3 back
8.710-881.0	373032	1/4"	12	.730"	1-forward, 3 back
8.710-885.0	373038	3/8"	4.0	.920"	1-forward, 3 back
8.710-884.0	373037	3/8"	5.5	.920"	1-forward, 3 back
8.710-886.0	373039	3/8"	8.5	.920"	1-forward, 4 back
8.710-883.0	373036	3/8"	12	.920"	1-forward, 4 back
8.710-882.0	373035	3/8"	14	.920"	1-forward, 4 back







0-forward, 3 back ports

1-forward, 3 back ports

1-forward, 4 back ports




- · Rotating sewer nozzle
- · Adds extra agitation
- 4,000 PSI
- Back Jet Only

Part #	Old No.	Rotating Nozzle	Size	Ports	
Rotating Sewer Nozzles					
8.710-899.0	373062	1/8"	5.5	0-forward, 3 back	
8.710-898.0	373061	1/4"	5.5	0-forward, 3 back	
8.710-900.0	373064	1/4"	8.0	0-forward, 3 back	
8.710-887.0	373040	1/4" Duct Clnr*	5.5	0-forward 2 side	

<sup>\*</sup>Duct Cleaner jet to sides instead of reverse







0-forward, 2 side ports

#### **Sewer Hose**

**SUPER FLEXIBLE SEWER LINE HOSE AND COUPLINGS** have small outside diameter, allowing hose and nozzles to fit through sewer line. Sewer line has super tough poly-ether cover over ultra-flexible nylon tube. (1/8" sewer nozzle

and hose will operate through many 1-1/2" lines.)
(Nozzles not included.)



- · 160°F max temperature
- Nylon tube, poly-ether cover
- 1.5 GPM optimum flow 1/8"
- 2.5 GPM optimum flow 1/4"

Part #	Old No.	Description		
1/8" hose - 4,800	0 PSI, 1/4"	inlet/1/8" outlet		
8.705-601.0	150960	1/8" x 25'		
8.705-602.0	150963	1/8" x 50'		
8.705-603.0	150964	1/8" x 100'		
1/4" Hose - 2,60	0 PSI, 1/4"	inlet/1/4" outlet		
8.705-607.0	150968	1/4" x 50'		
8.705-608.0	150970	1/4" x 100'		
1/4" Hose - 4,40	1/4" Hose – 4,400 PSI, 1/4" inlet/1/4" outlet			
8.705-610.0	150972	1/4" x 50'		
8.705-611.0	150973	1/4" x 100'		

# Foot Controlled Pressure Valve



Operators of sewer and tube cleaning equipment need both hands free to feed or retract the hose in the sewer line. Foot operated valve allows hands-free control.





- Inlet 3/8" outlet 1/4"
- Brass body stainless steel valve
- · Steel cover for safety
- Up to 12 GPM
- Up to 5,000 PSI

Part #	Old No.	Description	PSI
8.710-134.0	344200	Sewer Cleaner Foot Valve	3000
8.709-972.0	342024*	Foot Valve w/ ST-2305	5000
8.701-657.0	089006	Repair Kit - Foot valve	
8.701-673.0	089850	Repair Kit ST-2305	
8.711-526.0	4-0193	Kit, 25' Hose, #4.5 Nozzle,	Foot Valve

<sup>\*</sup>Heavy gauge steel construction for durability and stability

# ST-36 Pit Boss Sludge Sucker



Sludge Sucker uses a high pressure water stream (1,000-3,000 PSI) to suck the sludge off the bottom of pits or tanks and eject it through a 1-1/2" (15' long) hose to a disposal tank.

The base unit attaches to the end of a pressure washer lance with a quick coupler for extension to the bottom of the pit. Uses a 0° tip for suction/power ejection.



- Uses standard 1/4" MPT nozzle
- · Easy to change for different plumbing system flows and pressures

Part #	Old No.	Description
8.711-112.0	376137	ST-35 Pit Boss, 5.5 Nozzle/ 15' Hose
8.711-110.0	376126	(Base unit only)

<sup>\*</sup>w/o hose, nozzle or quick coupler (3/8" inlet port)

#### **Drum Tool Accessories**

The Indispensable Tools.



Part #	Old No.	Description	
8.712-534.0	449339	Drum Plug Wrench	
8.704-689.0	118400	Lid-Off	
8.704-691.0	118404	Funnel, 7" x 10"	
8.704-692.0	118407	3/4" Faucet	
8.704-693.0	118408	2" Faucet	
Load Cincher Ti	Load Cincher Tie Downs		
8.707-473.0	249938	7/8" x 5-1/2' (Non-Ratchet) "Quick Lock"	
8.707-474.0	249939	1" x 15' (Ratchet) "Tight Lock"	

# Fiberglass "Super Handles"

- · Tough, durable, lightweight
- · No cracking or splintering
- · No kinks or dents
- · Safer around electrical hazards
- · Easy-Twist cam lock extension
- Super heavy-duty aluminum alloy threads
- Standard 3/4" Acme thread fits: brooms, brushes, utility tools
- Optional reduction adapter for 3/4" to Acme standard

Part #	Old No.	Description
Super Handles		
8.709-306.0	306864	48" Length (4 ft)
8.709-307.0	306865	60" Length (5 ft)
8.709-308.0	306866	72" Length (6 ft)
Super-Extensio	n Handles	
8.709-309.0	306868	4 ft to 8 ft Ext
8.709-310.0	306869	6 ft to 12 ft Ext
8.709-311.0	306870	8 ft to 16 ft Ext
8.700-308.0	075271	Threaded Adapter

# **Drum/Tank Pump - Crank Type**

Chemical-resistant, lightweight pump, ideal for dispensing chemicals, pesticides and oils. **Polypropylene** for most alkalies, dilute acids, pesticides, and most oils & solvents. **Ryton** for extremely aggressive acids, aromatic and aliphatic hydrocarbons.



#### SPECIFICATION:

- 11 oz per revolution
- 6 GPM @ 70 RPM
- Viton seals
- · Polypropylene gasket
- 2" bung adapter
- · Outlet 3/4" barb 2 piece
- 47" suction tube
- · Weight 2.6 lbs

Part #	Old No.	Description
8.704-700.0	118435	Polypropylene Pump (Standard)
8.704-701.0	118438	Ryton Pump (Deluxe)
8.700-526.0	076975	Replacement Handles

# **Siphon Pumps**

Siphon liquids from higher to lower levels. Simply pump the bellows a few times to prime and start flow. Loosen air lock to stop.



- Drum pump fits 15, 30 & 55 gallon drums
- · Fit 2" bung opening
- Excellent for: Alkaline & acidic chemicals, diesel fuel, & oils
- Not for use with solvents!

Part #	Old No.	Description
8.704-698.0	118429	Red Hex Head (Heavy-duty)
8.704-696.0	118423	Red Head (Standard duty)
8.704-694.0	118420	Pail Pump (5 Gallon)

#### **Brushes**

**Rotating Brush** - Natural bristle (soft) used for painted surfaces. Nylon bristle (stiff) used for removing scum and grime on fiberglass boats, etc.



	17			
Part #	Old No.	Description		
Brush Unit Con	nplete			
8.709-312.0	306925	Natural		
8.709-314.0	306935	Nylon		
Replacement E	Replacement Brushes			
8.709-313.0	306927	Natural		
8.709-316.0	306937	Nylon		

#### Truck Wash Brush



- · Flag-tipped
- · Soft bristle
- ACME thread for Super Handles, or broom handles

Part #	Old No.	Description
8.709-298.0	306800	2-1/2" Bristle w/Bumper x 10"
8.709-303.0	306818	2-1/2" Bristle x 18"
8.709-304.0	306824	2-1/2" Bristle x 24"
8.709-305.0	306860	60" Flow-Thru Lance*

\*With Acme Thread & Garden Hose Attachment

# **Deck Scrub Brush – Over/Under -** Unique Heavy-duty Scrub Brush with Multi-Level/Angle.



- · Trimmed for cleaning hard-to-reach areas
- 10" molded polypropylene foam block does not warp or absorb water
- Stiff polypropylene bristle for aggressive cleaning
- · Excellent chemical resistance
- Use with threaded handle
- · Not a flow-thru

Part #	Old No.	Description
8.709-302.0	306812	Deck Scrub Brush

Tractor Brush - Soft for gentle cleaning of fine finishes.



Part #	Old No.	Description
8.709-300.0	306802	Flag Tip Window 10"

# **Compact Foamer**

# Legacy

Generates a high density clinging foam for extended dwell time to increase chemical action



- Stainless steel, aluminum and brass
- 1 to 5 GPM
- 195°F
- 2,500 PSI

•	5" long, 1'
	diameter

•	4 and 6.5
	nozzle
	included

Part #	Old No.	Description
8.903-998.0	344022V	1/8" F Inlet
8.903-999.0	344023V	1/4" F Inlet

NOTE: Most cleaning chemicals perform best when applied at 120° - 150°F and can be applied as a foam by adding a foaming agent. See your chemical supplier to obtain the correct product.

#### **Foam Cannon**

The ideal foam generator application accessory meters the foaming chemical for customized foam type and applies the foam to match the application.



- Stainless steel 1.5mm orifice (#5.5 nozzle equivalent)
- · Brass meter valve
- 3,000 PSI max pressure
- 4.8 GPM max flow
- · High impact glass-filled body
- · SS foam turbulator
- 176°F max temperature
- 1/4" FPT lance connect

Part #	Old No.	Description
8.710-125.0	344030	Foam Cannon/ Injector
8.710-126.0	344032	Foam Cannon/ Injector/Bottle

# **Air Power Sprayers**



- Pump-up style
- · Heavy-duty plastic sprayers for chemical applications
- Both models have adjustable nozzle from mist to solid stream
- 2 gallon unit has 2' hose and hand trigger
- · Excellent chemical resistance
- · Locking hand pump handle serves as carrying handle

Part #	Old No.	Description
8.704-703.0	118842	Thumb Button 3 Pint
8.704-702.0	118835	2 Gallon Sprayer

### **Foam Jet Kit**



Long distance foam applicator. Shoots over 20 feet of dense foam. Suction at 30 feet of height. Varable spray pattern.



- 5.000 PSI
- 5.6 GPM
- 14" inlet
- 140° F
- · Tubing length: 30 ft.

Part #	Description
8.750-296.0*	Kit, Foam Jet, 5,000 PSI, 5.6 GPM
8.750-429.0	Kit, Repair, Foam Jet O-rings/ SS Filter
8.750-430.0	Kit, Repair, Foam Jet, Hose/ Valve/ Filter

<sup>\*</sup> Includes tubing and fittings as shown

# **Lafferty Airless Foam Kit**



- · Machined stainless steel construction
- · Stainless steel chemical check valve
- Color-coded metering tips for up to 21 dilution ratios
- · Stainless steel quick disconnects
- 10' chemical tube with strainer
- 0° nozzle for increased foam throw distance

Part #	Water Flow Rate	@2,000 PSI	@ 137.9 bar	
8.749-908.0	Model 10	4.0 GPM	15.1 LPM	
8.749-909.0	Model 20	6.0 GPM	22.7 LPM	

# **Adjustable Foamer with Tank**

Control the foam spray angle with the variable fan nozzle.



- · Horizontal variable fan nozzle
- GPM: 5.3
- · Foam control adjustment knob
- 140°F
- PSI: 2,600

Part #	Description
8.710-124.0	Adjustable Foamer w/ Tank

#### **Thread Lock Products**



- Direct replacement for LocTite<sup>®</sup> and Fel-Pro™ products
- ND<sup>™</sup> anaerobic adhesives are liquid materials that cure to a solid, chemical-resistant plastic state when air is not present
- Excellent lubricant; prevents corrosion and fretting

		Size	
Nut Grade™	242	10 ml	
Nut Grade™	242	50 ml	
Nut Grade™	242	250 ml	
Stud Grade™	271	10 ml	
Stud Grade™	271	50 ml	
Penetrating Adhesive (Sealant)	290	10 ml	
	Nut Grade™ Nut Grade™ Stud Grade™ Stud Grade™	Nut Grade™         242           Nut Grade™         242           Stud Grade™         271           Stud Grade™         271	Nut Grade™         242         50 ml           Nut Grade™         242         250 ml           Stud Grade™         271         10 ml           Stud Grade™         271         50 ml

Nut Grade  $^{\rm TM}$  and Stud Grade  $^{\rm TM}$  are trademarks of the Oakland Corp. LocTite  $^{\rm I\!R}$  is a registered trademark of the LocTite Corp.

### **Gloves - Industrial Duty**

Industrial grade gloves for most industry needs chemical/ heat/ abrasion/laceration protection.



8.704-668.0 Gray – split cowhide work gloves, 2-1/2" gauntlet unlined. Great general purpose work glove.



8.704-669.0 Black, 14" PVC glove lined with cotton for the most demanding chemical handling.

Resists alkalines, acids

even works well as a sandblasting glove.

Part #	Old No.	Description
8.704-668.0	116105	Gray Roughout
8.704-669.0	116114	Black PVC

#### Rain Suit - 2 Piece



Part #	Old No.	Description
8.704-666.0	116100	Large
8.704-667.0	116101	Extra Large

#### **Amazing Pocket Reference - 3rd Edition**

A ton of information in a 5 oz book!



- Air & gases
- Automotive
- Chemistry
- Electrical
- · Physical constants
- Math
- · 3350 conversion factors
- · Plumbing & pipe
- Over 20 other subject areas

Part #	Old No.	Description
8.712-505.0	449015	Pocket Reference

### **Shipping Tape & Dispenser**

Big  $2^{\circ}$  x 110 yard rolls of clear. Biaxially-oriented polypropylene for secure packages.



 Heavy-duty tape dispenser with serrated blade

Part #	Old No.	Description
8.704-707.0	118916	Dispenser Boxed
8.901-249.0	118918	110 Yard Roll

# **Teflon® Thread Sealing Tape**



- Big 1/2" x 520" roll
- Mil spec #T27730

Part #	Old No.	Description
8.704-705.0	118905	Thread Sealing Tape