

LANDA®

Pressure Washer Equipment | Detergents | Parts & Accessories



1150 Davis Road, Suite J • Elgin, IL 60123
(800) 788-8867 • (847) 468-8800 • info@lorchem.com • www.lorchem.com

We Know How To Get Things **CLEAN**

PHW: *Top-of-the-Line, Industrial-Grade Hot Water Pressure Washer on Wheels*



For over a quarter of a century, the been the flagship of the Landa hot-water line packed with the highest industrial-quality and the most innovations—including low RPM Landa belt-drive tri-plunger pump with 7-year warranty, stainless steel top wrap, magnetic starter for long motor life, and optional time-delay shutdown, auto start-stop and LanCom wireless remote kit.



LANCOM WIRELESS REMOTE OPTION

In addition to its super-efficient horizontal Landa Duracoil, the PHW has among its traditional standard features: variable pressure wand, hour meter, adjustable thermostat, protection against thermal expansion, rust-free water tank, rust-free oil fuel tank, and tubed pneumatic tires for easy maneuvering.

The PHW has field-installable “Snap-N-Go” options.

PHW Features:

- Unitized structural base and frame provide excellent support and rigidity for years of service
- Oversized 10-gallon cross-linked polyethylene fuel tank with a ratcheting fuel cap to avoid stripping of threads; includes recessed fuel level gauge
- 13" tires provide excellent mobility and weight distribution with a combined load capacity of over 1,400 lbs.
- Large capacity 6-gallon water float tank with corrosion free durable PVC float valve
- Multi-port coil discharge manifold with built-in thermostat well and rupture disk assembly
- Cool-Bypass keeps pump water temperature low while in bypass

Model #	Part #	GPM	PSI	Pump RPM	Motor HP	Electrical V/Ph/Amp	Ship Weight
PHW3-11024D	1.109-078.0	2.8	1000	1725	2	120/1/20	590 lbs
PHW4-22024A	1.109-079.0	4.0	2200	1025	6.2	230/1/29	625 lbs
PHW4-22024B	1.109-080.0	4.0	2200	1025	6.2	230/3/19	610 lbs
PHW4-22024C	1.109-081.0	4.0	2200	1025	6.2	460/3/11	615 lbs
PHW4-22024F	1.109-082.0	3.5	2200	940	5	575/3/10	615 lbs
PHW4-22024G	1.109-083.0	4.0	2200	1025	6.2	208/1/31	625 lbs
PHW4-22024H	1.109-084.0	4.0	2200	1025	6.2	208/3/21	610 lbs
PHW4-30024A	1.109-085.0	3.9	3000	975	8.2	230/1/38	640 lbs
PHW4-30024B	1.109-086.0	3.9	3000	975	8.2	230/3/24	625 lbs
PHW4-30024C	1.109-087.0	3.9	3000	975	8.2	460/3/12	635 lbs
PHW4-30024F	1.109-088.0	3.5	3000	975	7.5	575/3/12	635 lbs
PHW4-30024G	1.109-089.0	3.9	3000	975	8.2	208/1/36	640 lbs
PHW4-30024H	1.109-090.0	3.9	3000	975	8.2	208/3/26	625 lbs
PHW5-30024B	1.109-091.0	4.8	3000	1500	10	230/3/30	625 lbs
PHW5-30024C	1.109-092.0	4.8	3000	1500	10	460/3/16	635 lbs

FIELD INSTALLED OPTIONS

Part #	Description
8.917-509.0	LanCom Snap-N-Go Wireless Remote Control Kit
8.725-709.0	Additional LanCom Remote
8.917-817.0	LanCom Wall Mount Bracket
8.917-507.0	Snap-N-Go Auto-Start/Stop Kit
8.917-508.0	Snap-N-Go Time Delay Kit
8.917-683.0	Steam Combo Kit
8.917-798.0	Caster Wheel Kit
8.917-713.0	Lifting Bracket/Hose Reel Platform with E-Zee Reel & Plumbing (holds 100' of 3/8" hose, not included)
8.917-714.0	Lifting Bracket/Hose Reel Platform Only
8.750-487.0	100' Landa Pivot Reel
8.750-477.0	100' Landa Non-Pivot Reel
8.711-858.0	175' Cox Hose Reel

- Corrosion-free polyethylene electrical box with easy access door and control panel is pre-wired with Snap-N-Go plugs for adding time delay, auto start/stop or Lan-Com wireless remote
- Tru-Trac pump rail belt adjustment keeps belt parallel with pump and motor when adjusting belt tension
- Removable fuel tank and end panels for unrestricted access to pump, unloader, motor, belts, and pulleys
- Recessed pockets in fuel tank allow for storage of spare parts, nozzle, cleaner, and even a can of pop
- Diagnostic lights notify the operator of incoming power, burner ignition, and motor overload
- Five tie-down points for safe transport
- Optional caster wheel kit
- Optional LanCom wireless remote now has feedback lights to indicate when burner and/or detergent injection are on

Outdoors | Electric Powered | Diesel/Oil Heated

HOT: *Economic, Portable, Electric-Powered Hot Water Pressure Washers*

The HOT is the most economical choice of LANDA's electric-powered, diesel-heated hot water pressure washers featuring a heat-efficient horizontal coil. Included in the series is a true steam cleaner or steamer, the HOT3-30036D, which produces extra-hot wet steam at up to 310° F.

HOT Features:

- LANDA high-pressure pump with 7-year warranty*
- High-efficiency SureFire burner mounted on the end for easy access
- Heavy-duty motor
- Quick-couple nozzle is made of hardened stainless steel
- 36 ft. of high-grade electrical cord with ground fault circuit interrupter
- Fatigue-free trigger gun with dual-lance variable pressure wand*
- 50 ft. of steel-wire braid high pressure hose*
- Schedule 80 coil with five-year warranty stainless steel top wrap*
- Water-resistant control panel with adjustable thermostat*
- Easy-to-attach downstream detergent injector for application of soap
- Many safety features, including rupture disk and thermal pump protector

Model #	Part #	GPM	PSI	Pump	RPM	Motor HP	Electrical V/Ph/Amp	Ship Weight
HOT2-11026D	1.109-093.0	2.0	1000	Axial	3450	1.5	120/1/18	425 lbs
HOT2-15026D	1.109-094.0	1.9	1500	Axial	3450	2	120/1/20	428 lbs
HOT2-11024D	1.109-095.0	2.0	1000	Direct	1725	1.5	120/1/18	434 lbs
HOT2-15024D	1.109-096.0	1.9	1500	Direct	1725	2	120/1/20	439 lbs
HOT3-11024D	1.109-097.0	2.8	1000	Direct	1725	2	120/1/20	530 lbs
HOT4-20024A	1.109-098.0	3.5	2000	Belt	1350	5	230/1/25	494 lbs
HOT4-20024G	1.109-099.0	3.5	2000	Belt	1350	5	208/1/27	494 lbs
Extra-Hot Steamer (310° F):								
HOT3-30036D	1.109-100.0	2.0	300	Axial	3450	1.5	120/1/12	425 lbs

FIELD INSTALLED OPTIONS

Part #	Description
8.917-506.0	Float Tank & Inlet Detergent Metering Valve
8.917-541.0	Lifting Bracket/Hose Reel Platform with E-Zee Reel & Plumbing (holds 100' of 3/8" hose, not included)
8.917-522.0	Lifting Bracket/Hose Reel Platform Only
8.750-487.0	100' LANDA Pivot Reel
8.750-477.0	100' LANDA Non-Pivot Reel
8.917-525.0	Caster Wheel Kit
9.802-283.0	Hour Meter (machine pre-wired for easy installation)



* HOT2-11026D and HOT2-15026D have an axial pump with 1-year warranty, yellow painted mild-steel top coil wrap, and 30 ft. high pressure hose with straight-through insulated wand. HOT3-30036D Steamer has high limit switch, axial pump with a 1-year warranty, and 50 ft. steam hose and wand.

SEHW: *Top-of-the-Line Electric-Powered Hot Water Pressure Washer in a Skid Frame*

The most rugged electric-powered hot-water pressure washer in a skid frame is the SEHW — short for Skid Electric Hot Water. With its durable, 1½ inch steel chassis, the engine and pump are vibration isolated from the frame for fatigue resistance and long life. The SEHW comes with a low-RPM LANDA belt-drive pump, time delay shutdown and extra-large diesel/fuel oil tank for hours of uninterrupted cleaning.



Model #	Part #	GPM	PSI	Pump RPM	Motor HP	Electrical V/Ph/Amp	Ship Weight
SEHW6-35024B	1.109-521.0	5.2	3500	1340	15	230/3/44	710 lbs
SEHW6-35024C	1.109-522.0	5.2	3500	1340	15	460/3/22	735 lbs

OPTIONS AND ACCESSORIES

Part #	Description
8.904-525.0	Wheel Kit, 4 Tires
8.903-504.0	Automatic Start / Stop*

* Replaces Time Delay Shutdown

Outdoors | Electric/Gasoline/Diesel Powered | Diesel/Oil Heated

COMPARISON CHART FOR ELECTRIC POWERED | DIESEL OR OIL HEATED

Feature	PHW	SEHW	HOT
Tri-Plunger LANDA High-Pressure Pump with 7-Year Warranty	Super-Duty	Super-Duty	Heavy-Duty*
Belt-Drive Pump Assembly	■	■	■HOT4-20024A,G only
Axial High-Pressure Pump with 1-Year Warranty			■*
Ground Fault Circuit Interrupter (1-phase only)	■	N/A	■
LANDA 5000 PSI Trigger Gun	■	■	■
1/2" Schedule 80 Horizontal Coil	■	■	■
Fuel Cap and Gauge	■	■	■
10-Gallon Fuel Tank	■	■	5 or 6 gallons depending on model
Durable Variable Pressure Wand	■	■	■
High-Pressure Detergent Injection	■	■	□
Polyethylene Float Tank	■	■	□
4 Hardened Stainless Steel Nozzles	■	■	
Oil/Water Separator in Fuel Line	■	■	
Magnetic Start Switch	■	■	
Stainless Steel Top Wrap	■	■	■*
2-Wire Tuff-Skin Hose Rated for 6000 PSI	□	■	□
Time Delay Shutdown	□	■	
Adjustable Thermostat	■	■	■
Hour Meter	■	■	□
Wet-Steam Combination	□	□	□
Auto Start-Stop	□	□	
Caster Wheel Kit	□		□
LanCom Wireless Remote	□		

* Applies only to specific models in series ■ = standard features □ = available options

COMPARISON CHART FOR GASOLINE OR DIESEL POWERED | DIESEL OR OIL HEATED

Feature	SLX	SLT	PDHW	PGHW	PGDC	MHP	MHC
Engine Fuel	Gasoline/Diesel	Gasoline/Diesel	Diesel	Gasoline	Gasoline	Gasoline	Gasoline
Engine Fuel Capacity	16/40 gallon	10/26 gallon	22 gallon	5 gallon**	5 gallon**	5 gallon**	1.5 gallon
LANDA 5000 PSI Trigger Gun	■	■	■	■	■	■	■
Burner	120V AC	120V AC	120V AC/12V DC	120V AC	12V DC	12V DC	12V DC
4 Hardened Stainless Steel Nozzles	■	■	■	■	■	■	■
Tri-Plunger LANDA Belt-Drive High-Pressure Pump	■	■	■	■	■	■	Direct Drive
Schedule 80 Horizontal Coil	3/4"	3/4"	1/2"	1/2**	1/2"	1/2"	1/2"
Dual Downdraft Steel Tube Vertical Coils							
Durable Variable Pressure Wand	■	■	■	■	■	■	■
Vibration Isolated Platform	■	■	■	■	■		
Electrical Generator	■	■	■	■			
High-Pressure Detergent Injection	■	■	□	■	□	□	
Polyethylene Float Tank	7.5 gallon	7.5 gallon	□	3.5 gallon	□	□	□
Stainless Steel Coil Wrap	■	■	□	□	□	□	□
Wet-Steam Combination	■	■	□	□			
2-Wire Tuff-Skin Hose Rated for 6000 PSI	■	■	■	■			
Oil/Water Separator in Fuel Line	■	■	■	■	□	□	□
Hour Meter	■	■	■	■			■
Adjustable Thermostat	■	■	■	■			■
AC Voltmeter	■	■					

* Model PGHW5-50524E uses a Schedule 160 coil made of 1/2-inch pipe **389cc models have 1.5 gallon gasoline tank ■ = standard features □ = available options

SLX & SLT: Largest Hot Water Washers Deliver 200°F Water and Dual-Gun Capability



Powered by industrial-duty Honda gasoline or water-cooled Kohler diesel engine, the LANDA SLX and SLT hot water pressure washers are as beefy as they come.

The SLX delivers up to 9.5 GPM of hot 200°F water and up to 2,500 PSI. It's ideal for multiple gun applications for a fast and furious clean.

The SLX has an extra large capacity 30-gallon diesel and 16-gallon gasoline steel fuel tanks (diesel model has a single 40-gallon fuel tank).

The SLT delivers up to 7.8 GPM and 3,200 PSI of hot water cleaning and a large 15-gallon diesel and 10-gallon gasoline tanks (26-gallon tank on diesel models).

Other features for these top-of-the-line models include:

- Low-RPM LANDA belt-drive pump with 7-year warranty
- 3/4" Schedule 80 coil with 5-year warranty
- Stainless steel coil cover
- Rugged steel tubing frame: 2" x 4" x 1/8" thick
- Oversize vibration isolators cushion engine and pump platform
- UL-1776 safety certification

Model #	Part #	GPM	PSI	Pump RPM	Engine	CCs	Engine Fuel	Ship Weight
SLX10-25324E	1.110-525.0	9.5	2500	1560	Honda GX660	688	Gasoline	2020 lbs
SLX10-25824E	1.110-526.0	9.5	2500	1470	Kohler KDW1003	1028	Diesel	2160 lbs

E = Electric start engine; battery not included

Model #	Part #	GPM	PSI	Pump RPM	Engine	CCs	Engine Fuel	Ship Weight
SLT6-32324E	1.110-520.0	5.9	3200	1570	Honda GX630	688	Gasoline	1245 lbs
SLT8-30324E	1.110-522.0	7.8	3000	1470	Honda GX660	688	Gasoline	1230 lbs
SLT6-32824E	1.110-521.0	5.9	3200	1470	Kohler KDW1003	1028	Diesel	1785 lbs
SLT8-30824E	1.110-523.0	7.8	3000	1560	Kohler KDW1003	1028	Diesel	1851 lbs

E = Electric start engine; battery not included



Buy with Confidence!



Unlike many of our competitors, LANDA's advertised specifications (PSI, GPM, etc.) are certified by the Cleaning Equipment Trade Association to be correct. And, of course, all LANDA equipment is ETL certified to UL-1776 safety standards.



PDHW: *Versatile Diesel Portable Hot Water Washer Adaptable to Specialized Applications*



Model #	Part #	GPM	PSI	Pump RPM	Engine	CCs	Burner Voltage	Ship Weight
PDHW5-35624E	1.110-060.0	4.7	3500	1125	Kubota Z602	599	12V DC	948 lbs
PDHW5-35624E/SS	1.110-061.0	4.7	3500	1125	Kubota Z602	599	12V DC	948 lbs.
PDHW5-35624E/G	1.110-062.0	4.7	3500	1125	Kubota Z602	599	120V AC	998 lbs.
PDHW5-35624E/G/SS	1.110-063.0	4.7	3500	1125	Kubota Z602	599	120V AC	998 lbs.

E = Electric start engine (battery not included); G = 2,900 watt generator; SS = Stainless steel frame

OPTIONS AND ACCESSORIES

Part #	Description
8.919-981.0	Float Tank with Inlet Injection Kit
9.802-225.0	Inlet Detergent Injector Kit
8.919-983.0	Hose Reel Platform Kit
8.919-990.0	Lift/Stack Platform Kit
8.920-298.0	Lift/Stack Platform Kit, Stainless Steel
8.919-985.0	Stainless Steel Drip Pan Kit
8.919-988.0	Emergency Air Shutoff Kit
8.919-989.0	Engine Spark Arrestor Kit
8.919-984.0	Lifting Sling Kit
8.904-525.0	Wheel Kit

LANDA's PDHW is a diesel-powered, hot water pressure washer that combines the versatility of a compact size with the ruggedness and cleaning power of a larger full-skid pressure washer. The PDHW delivers cleaning power of 3,500 PSI with a flow rate of 4.7 GPM.

The PDHW is packed with LANDA quality throughout. Powered by a reliable Kubota electric-start engine, the PDHW features a top-of-the-line, oil-bath, tri-plunger, belt-drive LANDA LT pump with 7-year warranty. The heating coil is made of ½-inch Schedule 80 cold-rolled pipe with a stainless steel outer top wrap. The sturdy steel frame gets all-weather protection from a polyester powder coat finish or stainless steel.

The PDHW is versatile with features and options that make it adaptable to specialized jobs. A 2,900 watt generator (on 120V burner models) provides power for the burner as well as a 120V outlet for low-wattage applications. The PDHW has forklift guides for transporting and brackets for mounting on a trailer. The extra-large, tilt-out, fuel tank provides hours of continuous cleaning. The PDHW has loads of additional options to make it the perfect machine for any job including off-shore oil rigs.

As with all LANDA models, the PDHW comes certified to the rigid UL-1776 safety standards, featuring: 24-inch hose guard for burst protection; thermal pump protector; high-temperature shutdown to prevent super-high heat build up; and rupture disk to vent any buildup of excessive pressure in the heating coil.



Outdoors | Gasoline Powered | Diesel/Oil Heated

PGHW: Classic, Portable Hot Water Washer — Our Most Popular Skid for 20+ Years

As LANDA's most popular gasoline-powered, industrial hot water pressure washer, the PGHW combines a smaller size with the ruggedness of a skid-mounted unit. Featuring a broad selection of models, including a 5,000 PSI model, the PGHW units are powered by a Honda, Vanguard or the liquid-cooled Kawasaki engine—all with electric start.



PGHW features:

- Stainless steel top wrap
- High-efficiency, easy-to-access burner and Schedule 80, Duracoil with 5-year warranty (Schedule 160 on 5,000 PSI model)
- Vibration isolated power platform with improved belt guard
- Low fuel shutdown protection
- LANDA belt-drive pump with 7-year limited warranty
- 2,000 watt Winco generator with an extra 120V power outlet
- Trailer ready with mounting brackets and 3-way valve to bypass float tank when drawing from an auxiliary tank
- Control panel can be placed on side or front of machine and includes hour meter low-fuel light and adjustable thermostat

Model #	Part #	GPM	PSI	Pump RPM	Engine	CCs	Ship Weight
PGHW4-30324E	1.110-048.0	3.5	3000	1125	Honda GX390	389	725 lbs
PGHW5-30224E	1.110-046.0	4.8	3000	1375	Vanguard 16	479	825 lbs
PGHW5-35324E	1.110-045.0	4.7	3500	1360	Honda GX630	688	840 lbs
PGHW4-40324E	1.110-047.0	4.0	4000	1425	Honda GX630	688	840 lbs
PGHW5-50524E	1.110-512.0	5.0	5000	1585	Kawasaki FD2750D	745	1285 lbs

E = Electric start engine; battery not included

OPTIONS AND ACCESSORIES

Part #	Description
8.904-525.0	4-Tire Wheel Kit (field installed, except PGHW5-50524E)
8.904-534.0	4-Tire Wheel Kit (field installed, PGHW5-50524E)
8.916-588.0	Stainless Steel Bottom Wrap (factory installed)
8.916-585.0	Steam Valve Kit (field installed)
8.915-496.0	LANDA 360° Pivot Hose Reel Kit (100 ft capacity)
8.903-522.0	LANDA Non-Pivot Hose Reel Mounting Kit (100 ft capacity)
8.711-858.0	175 ft Cox Hose Reel
9.804-067.0	100 ft E-Zee Hose Reel
8.749-946.0	Vinyl Skid Cover (except PGHW5-50524E)

- Patent-Pending Cool-Bypass keeps pump water temperature low while in bypass
- Single-side access to 5-gallon gasoline and 10-gallon diesel fuel tanks
- Rugged 1½-inch square tube steel frame
- Easy-to-winterize float tank with upstream detergent injection

The PGHW5-50524E standard features include Schedule 160 coil, stainless steel top wrap, 5,000 PSI straight-thru wand and steam valve.

PGDC: Affordable, Yet Rugged, Skid Pressure Washer with 12VDC Burner System

The PGDC provides an economical alternative to the skid-mounted family without sacrificing super duty ruggedness.

All three models are powered by electric-start Honda or Vanguard engines and, with a belt-drive LANDA pump, deliver up to 3,500 PSI in cleaning power. Water is heated by a high-efficiency 12VDC burner assembly (battery not included.)



Model #	Part #	GPM	PSI	Pump RPM	Engine	CCs	Ship Weight
PGDC4-35324E	1.110-049.0	3.8	3500	1185	Honda GX390	389	697 lbs
PGDC5-35224E	1.110-050.0	4.7	3500	1185	Vanguard 16	479	630 lbs
PGDC5-35324E	1.110-051.0	4.7	3500	1185	Honda GX630	688	650 lbs

E = Electric start engine; battery not included

OPTIONS AND ACCESSORIES

Part #	Description
8.916-588.0	Stainless Steel Bottom Wrap (factory installed)
8.916-606.0	Float Tank with Inlet Detergent Metering Valve
8.904-525.0	Wheel Kit
8.915-496.0	LANDA 360° Pivot Hose Reel Kit (100 ft capacity)
8.903-522.0	LANDA Non-Pivot Hose Reel Mounting Kit (100 ft capacity)
8.711-858.0	175 ft Cox Hose Reel
9.804-067.0	100 ft E-Zee Hose Reel
8.749-946.0	Vinyl Skid Cover

PGDC features:

- Schedule 80 Duracoil with 5-year warranty and stainless steel top wrap
- Vibration isolated platform
- Rugged 1½-inch square tube steel frame
- Insulated variable pressure wand

Outdoors | Gasoline Powered | Diesel/Oil Heated

MHP: Economy Line Mini-Skid with Extra-Narrow Frame for Moving Through Doorways

The MHP is an economy mini-skid, hot-water pressure washer with an extra narrow frame for maneuvering through doorways.

Less than 25-inches in width, the four MHP models are powered by Honda and Vanguard engines and feature a 12VDC burner system.

The MHP features a narrow-frame chassis made of rugged 1¼-inch square steel tube, a Schedule 80 heating coil, easy-to-remove side panels for convenience in servicing, a



Shown with optional hose reel and wheel kit

Model #	Part #	GPM	PSI	Pump RPM	Engine	CCs	Ship Weight
MHP4-30324E	1.110-501.0	3.5	3000	1160	Honda GX340	389	555 lbs
MHP4-35324E	1.110-503.0	3.8	3500	1185	Honda GX390	389	545 lbs
MHP4-35224E	1.110-502.0	3.8	3500	1185	Vanguard 16	479	525 lbs

E = Electric start engine; battery not included

OPTIONS AND ACCESSORIES

Part #	Description
8.903-530.0	Stainless Steel Outer Wrap
8.931-276.0	Stainless Steel Top Wrap with Black Bottom Wrap
8.903-596.0	Float Tank and Inlet Detergent Metering Valve
8.904-514.0	100', 360° Pivot Hose Reel (shown)
8.904-533.0	Wheel Kit (4 Caster Wheels)

LANDA belt-drive pump, variable pressure wand and downstream detergent injection.

MHC: Rugged On-Site Hot Water Pressure Washer on Wheels with 12VDC Burner System

The MHC combines LANDA's ruggedness with portability to deliver a very popular hot water washer.

Featuring a power range of up to 3.5 GPM and 3,500 PSI, the MHC features a beefy frame made of 1¼-inch square steel tubing, stainless steel top wrap, 13" tires for stability and ease in maneuvering, and a LANDA direct-drive high-pressure pump. The easy-access 12VDC burner and Schedule 80 coil make the MHC a tech's dream.

MHC features:

- Stainless steel top wrap
- Conveniently placed control panel with adjustable thermostat and hour meter
- 10 gallon diesel translucent fuel tank
- 50 ft. of high pressure hose with variable pressure wand
- Optional float tank with inlet detergent metering valve
- Optional caster wheel kit



Model #	Part #	GPM	PSI	Pump RPM	Engine	CCs	Ship Weight
MHC3-25124	1.110-037.0	2.5	2500	3400	Subaru EX21	211	550 lbs
MHC3-30324	1.110-038.0	3.0	3000	3400	Honda GX270	270	575 lbs
MHC4-30324	1.110-039.0	3.5	3000	3400	Honda GX340	389	590 lbs
MHC4-30324E	1.110-040.0	3.5	3000	3400	Honda GX340	389	595 lbs
MHC4-30324E/S	1.110-041.0	3.5	3000	3400	Honda GX390	389	600 lbs
MHC4-35324E	1.110-042.0	3.5	3500	3400	Honda GX390	389	600 lbs

E = Electric start engine; battery not included *S = Designed for high altitude applications

OPTIONS AND ACCESSORIES

Part #	Description
8.915-404.0	Caster Wheels (front)
8.915-406.0	Float Tank & Inlet Detergent Valve
8.915-496.0	360° Pivot Hose Reel Kit (100' cap.)
8.917-541.0	Lifting Bracket/Hose Reel Platform with E-Zee Reel & Plumbing (holds 100' of 3/8" hose, not included)
8.917-522.0	Lifting Bracket/Hose Reel Platform Only
8.750-487.0	100' LANDA Pivot Reel
8.750-477.0	100' LANDA Non-Pivot Reel
8.916-184.0	Lifting Bracket
8.915-494.0	Trailer Mount Kit

Indoors | Electric Powered | Natural Gas or LP Gas Heated

VNG: Industry's Most Rugged, Reliable and Versatile Natural Gas-Heated Hot Water Series

Model #	Part #	GPM	PSI	Pump RPM	Motor HP	Electrical V/Ph/Amp	Approx BTU	Ship Wt
VNG4-20024A	1.109-563.0	4.0	2200	930	6.2	230/1/27	400,000	1010 lbs
VNG4-20024B	1.109-564.0	4.0	2200	930	6.2	230/3/15	400,000	990 lbs
VNG4-20024C	1.109-565.0	4.0	2200	930	6.2	460/3/8	400,000	990 lbs
VNG4-20024H	1.109-568.0	4.0	2200	930	6.2	208/3/18	400,000	1000 lbs
VNG4-30024A	1.109-569.0	3.9	3000	775	8.2	230/1/36	400,000	1030 lbs
VNG4-30024B	1.109-570.0	3.9	3000	775	8.2	230/3/25	400,000	1030 lbs
VNG4-30024C	1.109-571.0	3.9	3000	775	8.2	460/3/15	400,000	1030 lbs
VNG4-30024H	1.109-574.0	3.9	3000	775	8.2	208/3/27	400,000	1010 lbs
VNG6-30024B	1.109-575.0	6.0	3000	1525	15	230/3/39	600,000	1830 lbs
VNG6-30024C	1.109-576.0	6.0	3000	1525	15	460/3/19	600,000	1830 lbs
VNG8-30024B	1.109-579.0	8.0	3000	1370	20	230/3/52	750,000	1845 lbs
VNG8-30024C	1.109-580.0	8.0	3000	1370	20	460/3/26	750,000	1845 lbs
VNG8-30024H	1.109-582.0	8.0	3000	1370	20	208/3/54	750,000	1845 lbs
VNG10-20024B	1.109-559.0	10	2000	1630	20	230/3/46	935,000	1925 lbs
VNG10-20024C	1.109-560.0	10	2000	1630	20	460/3/23	935,000	1925 lbs

OPTIONS AND ACCESSORIES

Part #	Old Part #	Description
--------	------------	-------------

LP-GAS CONVERSION KITS

9.801-019.0	35-210	Kit to Convert Fuel to LP Gas (for models up to 4 GPM)
8.904-068.0	35-212	Kit to Convert Fuel to LP Gas (for models over 4 GPM)
9.802-633.0	7-1010	LP Regulator Assembly

REMOTE STATIONS

8.903-465.0	30-421	Remote Station for Time Delay Unit
8.903-464.0	30-420	Remote Station for Auto Start / Stop Unit
<u>VNG can support up to 3 additional stations. Part #30-420 or #30-421 must be installed first:</u>		
8.905-686.0	6-0388	Additional Control Box for Time Delay Unit
8.905-688.0	6-0389	Additional Control Box for Auto Start / Stop Unit

LANCOM WIRELESS REMOTE

8.930-376.0	LanCom Wireless Remote Control System	
8.941-545.0	Additional Remote	
8.930-131.0	Wall Mount Bracket for Fixed LanCom Remote	

OTHER OPTIONS

8.903-512.0	30-490	Auto Start / Stop (for models up to 6 GPM) [Replaces Time Delay Feature]
8.903-513.0	30-491	Auto Start / Stop (for 8 GPM model) [Replaces Time Delay Feature]
9.801-040.0	7-10031	Draft Diverter, 10" (for models up to 4 GPM)
8.717-730.0	7-10032	Draft Diverter, 12" (for models over 4 GPM)

The natural gas VNG offers a number of features, such as time-delay shutdown, efficient vertical coil and burner assembly, Schedule 80 Duracoil with 5-year warranty and 24V electronic ignition.



Models can be fitted for LP gas and can provide wet steam combination.

The VNG 6-3000 and 8-3000 models are designed for multiple operating stations. Each of these units is equipped with a modulating gas valve, which adjusts the gas flow to keep the water temperature even when one to four guns are in use at one time.

Remote operation is available with support for up to four wired remote stations or with the LanCom wireless remote control option. (LanCom wireless remote available only on time-delay equipped models.)

Indoors | Electric Powered | Natural Gas or LP Gas Heated

VHG: Extra-Compact Natural Gas or LP-Heated Stationary Hot Water Pressure Washer

LANDA's extra-compact natural gas model is the VHG, a heavy duty stationary unit that fits within a footprint of only 24" and 53" (35" by 66" for 15 and 20 HP models).

The VHG produces cleaning power of up to 3,000 PSI, 8 GPM and can be equipped with LANDA's optional LanCom wireless remote system*.



VHG features:

- Insulated variable pressure wand and trigger gun
- Leak-free hot water coil made of Schedule 80, cold-rolled steel pipe
- Electronic ignition standard on all models
- Brass, anti-syphon detergent metering valve for dispensing precise amount of cleaning agent
- Hinged side cover allowing easy access to pump and unloader valve



Shown with optional stainless steel and LanCom wireless remote

*Wireless remote available only on time-delay equipped models.

Model #	Part #	GPM	PSI	Pump RPM	Motor HP	Electrical V/Ph/Amp	Approx BTU	Ship Wt
VHG4-20024A	1.109-534.0	3.5	2000	1175	5	230/1/25	350,000	750 lbs
VHG4-22024A	1.109-535.0	4.0	2200	835	6.2	230/1/27	400,000	790 lbs
VHG4-22024B	1.109-536.0	4.0	2200	835	6.2	230/3/15	400,000	770 lbs
VHG4-22024C	1.109-537.0	4.0	2200	835	6.2	460/3/8	400,000	780 lbs
VHG4-22024G	1.109-538.0	4.0	2200	835	6.2	208/1/29	400,000	790 lbs
VHG4-22024H	1.109-539.0	4.0	2200	835	6.2	208/3/18	400,000	780 lbs
VHG4-30024A	1.109-541.0	3.9	3000	775	8.2	230/1/36	400,000	868 lbs
VHG4-30024B	1.109-542.0	3.9	3000	775	8.2	230/3/25	400,000	815 lbs
VHG4-30024C	1.109-543.0	3.9	3000	775	8.2	460/3/15	400,000	815 lbs
VHG4-30024G	1.109-544.0	3.9	3000	775	8.2	208/1/38	400,000	815 lbs
VHG4-30024H	1.109-545.0	3.9	3000	775	8.2	208/3/27	400,000	815 lbs
VHG5-30024B	1.109-546.0	4.8	3000	1035	10	230/3/29	480,000	780 lbs
VHG5-30024C	1.109-547.0	4.8	3000	1035	10	460/3/14	480,000	835 lbs
VHG5-30024H	1.109-548.0	4.8	3000	1035	10	208/3/30	480,000	780 lbs
VHG6-30024B	1.109-549.0	6.0	3000	1525	15	230/3/39	600,000	1675 lbs
VHG6-30024C	1.109-550.0	6.0	3000	1525	15	460/3/19	600,000	1675 lbs
VHG8-30024B	1.109-552.0	8.0	3000	1370	20	230/3/52	750,000	1845 lbs
VHG8-30024C	1.109-553.0	8.0	3000	1370	20	460/3/26	750,000	1845 lbs

OPTIONS AND ACCESSORIES

Part #	Old Part #	Description
OPTIONS AVAILABLE FOR ALL MODELS:		
8.903-489.0	30-4440	Time Delay Shutdown
8.905-686.0	6-0388	Extra Remote Box (with or without Time Delay)
9.802-633.0	7-1010	LP Gas Regulator Assembly
8.941-616.0		LanCom Wireless Remote System (Must be ordered with Time Delay Shutdown)
8.941-545.0		Additional LanCom Remote
8.930-131.0		Wall Mount Bracket for Fixed LanCom Remote
OPTIONS AVAILABLE FOR MODELS UP TO 5 GPM:		
8.903-474.0	30-4331	Remote Operation and Time Delay Shutdown
8.903-472.0	30-4330	Remote Operation for One Wash Station Standard
9.801-040.0	7-10031	Draft Diverter, 10"

Part #	Old Part #	Description
9.801-019.0	35-210	LP Conversion Kit
8.903-541.0	30-5162	Stainless Steel Coil Wrap, 4-Panel Skirt and Cover
8.903-542.0	30-51621	Stainless Steel Coil Wrap and Motor Cover Only
8.903-543.0	30-5163	Wheeled Cart for VHG Propane Model
OPTIONS AVAILABLE FOR MODELS OVER 5 GPM:		
8.903-477.0	30-4333	Remote Operation and Time Delay Shutdown
8.903-476.0	30-4332	Remote Operation for One Wash Station Standard
8.717-730.0	7-10032	Draft Diverter, 12" (15 and 20 HP models)
8.904-068.0	35-212	LP Conversion Kit (15 and 20 HP models)
8.903-545.0	30-5166	Stainless Steel Coil Wrap, 4-Panel Skirt and Cover
8.903-546.0	30-51661	Stainless Steel Coil Wrap and Motor Cover Only

VHP: The Only LP-Heated Model That Is Also Portable for Moving About the Shop

The VHP is the solution when portability is needed indoors. Featuring a carrier with snug-fit band for a 10-gallon LP tank, the VHP easily maneuvers on tubed pneumatic tires.

The VHP is built with a heavy-duty electric motor and belt-driven tri-plunger LANDA pump. It is designed for **vapor type propane only**. Other features include variable pressure wand, direct-spark piezo ignitor, 10 feet of gas hose, downstream detergent injection and ground-fault circuit interrupter.



Model #	Part #	GPM	PSI	Pump RPM	Motor HP	Electrical V/Ph/Amp	Approx BTU	Ship Wt
VHP2-15024D	1.109-556.0	1.8	1500	1100	2	120/1/17	140,000	470 lbs
VHP3-20024A	1.109-557.0	2.5	2000	1375	5	230/1/20	245,000	500 lbs

OPTIONS AND ACCESSORIES

Part #	Old Part #	Description
8.903-538.0	30-516	Stainless Steel Outer Wrap & Pump Motor Cover
8.903-501.0	30-470	Electronic Ignition (Convenience in Lighting Pilot)

Indoors | Electric Powered | Electric Heated

EHW: Ideal Indoor Hot Water Washer — No Fumes, No Noise, Works and Fits In a Closet

The EHW is ideal for in-plant cleaning needs. Just plug it in and get hot water...no noise, no fumes. It can be located under a stairway or inside a closet.

Featuring a unique design, the stainless steel heating coil is immersed in a tank of hot water so the heating elements never touch the pressurized water—reducing scale build up and maintenance. A layer of oil sets atop the enclosed tank of water for additional heat retention and prevention of evaporation.

Hot water spray is generated virtually on demand by simply pulling the spring-loaded trigger.



Model #	Part #	GPM	PSI	Pump RPM	Motor HP	Electrical V/Ph/Amp	KW	Ship Weight
EHW4-20024C	1.109-500.0	4.2	2000	935	6.2	460/3/55	40.5	620 lbs
EHW4-30024C	1.109-501.0	3.5	3000	800	7.5	460/3/59	40.5	640 lbs

OPTIONS AND ACCESSORIES

Part #	Description
8.930-163.0	LanCom Wireless Remote Control System, 1-Step Detergent
8.930-177.0	LanCom Wireless Remote Control System, 2-Step Detergent
8.930-358.0	Additional Remote
8.930-131.0	Wall Mount Bracket for Fixed LanCom Remote

EHW features:

- LanCom wireless remote control option with injection of one or two chemicals
- Time-delay shutdown for protection against operator neglect
- 7-day timer to automatically turn on or off heating elements
- ETL certification to rigid UL safety standards

COMPARISON CHART FOR ELECTRIC POWERED | NATURAL GAS, LP GAS OR ELECTRIC HEATED PRESSURE WASHERS

Feature	VNG	VHG	VHP	EHW
Tri-Plunger Landa High-Pressure Pump with 7-Year Warranty	Super-Duty	Super-Duty	Heavy-Duty	Super-Duty
Heating Source	Natural Gas/LP	Natural Gas/LP	LP Gas	All-Electric
Belt-Drive Pump Assembly	■	■	■	■
LANDA 5000 PSI Trigger Gun	■	■	■	■
Durable Variable Pressure Wand	■	■	■	■
Schedule 80 Coil	■	■	■	NA
Magnetic Start Switch	■	■		■
Adjustable Thermostat	■	■		■
4 Hardened Stainless Steel Nozzles	■	■		■
High-Pressure Detergent Injection	■	■		
3.5 Gallon Polyethylene Float Tank or Larger	■	■		
Electronic Ignition (no standing pilot light)	■	■	□	
2-Wire Tuff-Skin Hose Rated for 6000 PSI	■	□	□	■
Time Delay Shutdown	■	□		■
Hour Meter	■			
Wet-Steam Combination	■			
Ground Fault Circuit Interrupter (1-phase only)	NA		■	NA
LP Gas Conversion	□	□	■	NA
Remote Control	□	□		□

NA = not applicable ■ = standard features □ = available options

Outdoors/Indoors | Gasoline, Diesel or Electric Powered | Belt-Driven Pump

MP & MPE: *Portable Cold Water Washer w/ Roll Cage Protection and up to 5000 PSI Cleaning*

There are no other cold-water pressure washers with more blasting power than the MP and MPE.

Powered by a 389 or 688cc Honda engine, a 401cc Kohler engine or 20 HP Baldor Motor, and coupled to a tri-plunger LANDA pump, the MP and MPE deliver an extra-powerful spray of up to 5,000 PSI.

The MP and MPE are construction-site ready with a rugged roll cage and lifting bar.

MP & MPE features:

- High-impact steel roll cage with lifting beam
- Protected by electrostatic, powder-coat, epoxy paint
- 50 ft. of high pressure hose rated for up to 6,000 PSI
- Two or four 13-inch, tubed, pneumatic tires for all-terrain maneuvering



Tandem Axle Gasoline Powered Model: MP-455034E



Tandem Axle Electric Powered Model: MPE5-50024B



Single-Axle Gasoline Powered Model: MP-373534

Model #	Part #	GPM	PSI	Pump RPM	Engine	CCs	Engine Fuel	Ship Weight
MP-373534	1.107-001.0	3.7	3500	1185	Honda GX390	389	Gasoline	295 lbs
MP-455034E	1.107-002.0	4.5	5000	1185	Honda GX660	688	Gasoline	415 lbs
MP-343084E	1.107-082.0	3.4	3000	1185	Kohler KD420	401	Diesel	430 lbs

E = Electric start engine; battery not included. Also this is a tandem axle model.

Model #	Part #	GPM	PSI	Pump RPM	V/Ph/Amp Electrical	Motor HP	Ship Weight
MPE5-50024B	1.106-001.0	5.0	5000	1900	230/3/48	20	534 lbs
MPE5-50024C	1.106-002.0	5.0	5000	1900	460/3/26	20	534 lbs

OPTIONS AND ACCESSORIES

Part #	Old Part #	Description
9.801-028.0	35-358	EZ Hose Reel Kit, 100 ft. (for single axle model)
9.801-029.0	35-359	Non-Pivot Hose Reel Kit, 100 ft. (for tandem axle model)

COMPARISON CHART FOR GASOLINE & ELECTRIC POWERED COLD WATER PRESSURE WASHERS

Feature	MP/MPE	SEA	PG/PE	PC/PDE	PGA	PCA	PD	ZEF	ZG/ZE
Tri-Plunger LANDA High-Pressure Pump with 7-Year Warranty	Super-Duty	Super-Duty	Super-Duty	Heavy-Duty	Heavy-Duty	Heavy-Duty	Heavy-Duty*	Heavy-Duty*	Heavy-Duty*
Axial High-Pressure Pump with 1-Year Warranty							■*		■*
Tubed Pneumatic Tires	■		■	■	■	■			
Accepts Incoming Hot Water	■	■	■	■	■	■*	■	■*	
Ground Fault Circuit Interrupter (1-phase electric models only)		■	■PE Only	■PDE Only			■	■	ZE
Downstream Chemical Injector	■	■	■	■				■	
4 Hardened Stainless Steel Nozzles	■	■	■	■	■	■			
Easy-Start Valve (265cc and above gasoline models only)	■	■	■		■	■			
LANDA 5000 PSI Trigger Gun	■	■	■						
Belt-Drive Pump Assembly	■	■	■		■				
2-Wire Tuff-Skin Hose Rated for 6000 PSI	■	■	■						
Magnetic Start Switch (electric models only)	■	■	■						
Time Delay Shutdown		■							
Auto Start-Stop		□							■ with wall switch
Durable Variable Pressure Wand	■MP-373534 only	■	■PG models over 3000 PSI only						
Spring-Loaded Shock-Absorbing Feet			■		■				
Heavy-Duty Roll Cage	■								

* Applies only to specific models in series

■ = standard features

□ = available options

Outdoors/Indoors | Gasoline or Electric Powered | Belt-Driven Pump

SEA: Super-Duty Cabinet-Design Cold Water Model Offers Quiet, Flexible Indoor Cleaning

The SEA is the top-of-the-line stationary, cold-water pressure washer.

All models are belt-driven with top-quality LANDA pumps and feature time delay shutdown or optional auto start/stop.

Remote operation is available with the LanCom wireless remote control option.

Other features include insulated, variable pressure wand, 50 ft. hose rated for up to 6,000 PSI, thermal pump protection, handles water up to 175°F, stainless steel cabinet and inlet filtration.



Model #	Part #	GPM	PSI	Pump RPM	Electrical V/Ph/Amp	Motor HP	Ship Weight
SEA3-11024D	1.106-500.0	2.8	1000	1540	120/1/20	2	210 lbs
SEA4-20024A	1.106-501.0	4.2	2000	935	230/1/28	6.2	280 lbs
SEA4-20024B	1.106-502.0	4.2	2000	935	230/3/16	6.2	220 lbs
SEA4-20024C	1.106-503.0	4.2	2000	935	460/3/7.2	6.2	220 lbs
SEA4-20024G	1.106-505.0	4.2	2000	900	208/1/30	6.2	297 lbs
SEA4-20024H	1.106-506.0	4.2	2000	900	208/3/18.5	6.2	220 lbs
SEA4-30024B	1.106-507.0	3.5	3000	800	230/3/21.5	7.5	235 lbs
SEA4-30024C	1.106-508.0	3.5	3000	800	460/3/10.5	7.5	235 lbs



Optional stainless steel wheel kit, detergent jug rack and E-Zee hose reel



OPTIONS AND ACCESSORIES

Part #	Old Part #	Description
8.930-163.0		LanCom Wireless Remote Control, 1-Step Detergent†
8.930-177.0		LanCom Wireless Remote Control, 2-Step Detergent†
8.930-358.0		Additional Remote
8.930-131.0		Wall Mount Bracket for Fixed LanCom Remote
9.801-034.0	35-560	Floor Stand
8.903-617.0	30-635	Floor Stand (stainless steel)
9.801-035.0	35-563	Caster Wheels (Fits 35-560 Floor Stand)
9.801-036.0	35-565	E-Zee Hose Reel Kit (Fits 35-560 Floor Stand)

Part #	Old Part #	Description
8.903-619.0	30-640	Wall Mount Bracket Assembly (stainless steel)
9.802-265.0	4-02750003	Hose Reel, Mini, 100 ft. (Fits Wall Bracket)
8.711-860.0	4-02750002	Hose Reel, Mini, 50 ft. (Fits Wall Bracket)
8.904-527.0	4-03177	Wheel Kit with Detergent Rack (stainless steel)
8.903-521.0	30-5020	E-Zee Hose Reel & Mounting Kit (Fits Wheel Kit)
8.903-461.0	30-415	Remote On/Off Switch Option (Time-Delay units only)††
8.903-448.0	30-332	Float Tank Option with Inlet Soap Injection**
8.903-511.0	30-487	Automatic Start / Stop**††

* Float Tank cannot be ordered with Wheel Kit ** Replaces Time Delay Shutdown † LanCom Remote option not compatible with Auto Start/Stop or Float Tank options †† Not compatible with LanCom

PG & PE: LANDA's Most Popular Belt-Drive Model for Constant Usage Applications

The PG and PE are the workhorses of LANDA's cold water pressure washer line offering a broad range of super duty cleaning, from 1,000 to 4,000 PSI.

PG & PE features:

- Insulated variable pressure wand (PG models over 3,000 PSI only)
- Two spring-loaded feet to absorb vibration;
- Thermal pump protection
- E-Z start valve on all PG models
- LANDA belt-drive pump with 7-year warranty
- 13-inch tubed pneumatic tires for easy maneuvering
- 50 ft. of Tuff-Flex hose rated for up to 5,000 PSI



PG



PE

Model #	Part #	GPM	PSI	Pump RPM	Engine	CCs	Ship Weight
PG4-20324	1.107-010.0	4.2	2000	1300	Honda GX270	270	230 lbs
PG4-35324	1.107-011.0	3.7	3500	1185	Honda GX390	389	250 lbs
PG5-35224E	1.107-013.0	4.7	3500	1185	Vanguard 16	479	275 lbs
PG4-40324E	1.107-012.0	4.0	4000	1190	Honda GX630	688	275 lbs

E = Electric start; battery not included

Model #	Part #	GPM	PSI	Pump RPM	Electrical V/Ph/Amp	Motor HP	Ship Weight
PE3-11024D	1.106-009.0	2.8	1000	1540	120/1/20	2	155 lbs
PE4-20024A	1.106-010.0	4.2	2000	900	230/1/27	6.2	285 lbs
PE4-20024B	1.106-011.0	4.2	2000	900	230/3/16	6.2	265 lbs
PE4-20024C	1.106-012.0	4.2	2000	900	460/3/8	6.2	230 lbs
PE4-30024A	1.106-013.0	3.5	3000	800	230/1/36	7.5	270 lbs
PE4-30024B	1.106-014.0	3.5	3000	800	230/3/21.5	7.5	290 lbs
PE4-30024C	1.106-015.0	3.5	3000	800	460/3/10.5	7.5	280 lbs
PE5-30024B	1.106-016.0	4.8	3000	1060	230/3/26.8	10	290 lbs
PE5-30024C	1.106-017.0	4.8	3000	1060	460/3/13.4	10	285 lbs

Outdoors/Indoors | Gasoline or Electric Powered | Direct-Driven Pump

PC & PDE: LANDA's Toughest Direct-Drive Cold Water Pressure Washers

The PC & PDE pressure washers offer a similar breadth of cleaning selection as the PG & PDE except with direct-drive instead of belt-drive pumps.

All PC models are powered by Honda or Subaru engines with recoil start while PDE models feature industrial-grade motors.



PC



PDE

PC & PDE features:

- 50 feet of wire-braid high-pressure hose
- E-Z start valve on PC models with 265cc or more gasoline engine
- 36 ft. cord with operator-protecting Ground Fault Circuit Interrupter for 1-phase PDE models
- Two rubber feet to absorb vibration and keep the unit from "walking" while in operation

Model #	Part #	GPM	PSI	Pump RPM	Engine	CCs	Ship Weight
PC3-24324	1.107-005.0	2.3	2400	3200	Honda GX160	163	130 lbs
PC3-27324	1.107-006.0	2.5	2700	3200	Honda GX200	196	135 lbs
PC3-30124	1.107-007.0	3.0	3000	3200	Subaru EX27	265	150 lbs
PC4-35324	1.107-008.0	3.8	3500	3200	Honda GX390	389	185 lbs

Model #	Part #	GPM	PSI	Pump RPM	Electrical V/Ph/Amp	Motor HP	Ship Weight
PDE2-11024D	1.106-003.0	2.0	1000	3450	120/1/15	1.5	95 lbs
PDE2-15024D	1.106-004.0	1.8	1300	3450	120/1/20	2	145 lbs
PDE4-20024A	1.106-005.0	3.5	2000	3450	230/1/20	5	170 lbs
PDE4-30025B*	1.106-007.0	3.5	3000	3450	230/3/21.5	7.5	225 lbs
PDE4-30025C*	1.106-008.0	3.5	3000	3450	460/3/11	7.5	225 lbs

*Available only until current inventory of build components is depleted. Has AR pump.

- Insulated, two-piece, straight-through wand
- Nickel plated handles on front and back for easy loading
- Thermal pump protector to prevent overheating in bypass mode

Outdoors/Indoors | Gasoline or Electric Powered | Aluminum Frame

PGA & PCA: Portable Aluminum Chassis Cold Water Pressure Washers

The PGA and PCA are LANDA's aluminum frame, cold water pressure washer lines. The PGA series features belt-drive models offering cleaning power of up to 3,500 PSI at 3.7 GPM. The PCA series features direct-drive models offering cleaning power of up to 3,500 PSI at 3.8 GPM.

Both are easy to transport, as well as push or pull around, thanks to their innovative frame construction and ideal weight distribution. The corrosion-resistant aluminum frame makes these models much lighter to lift into a vehicle; handles on both front and back make for easier loading; and the cast aluminum rotary joints allow the main handle to fold down making the PGA and PCA more compact. All PGA and PCA models are powered by Honda engines with recoil start and 3-year warranty coupled with tri-plunger, high-pressure LANDA pumps with 7-year warranty.



PGA



PCA



Model #	Part #	GPM	PSI	Pump RPM	Engine	CCs	Ship Weight
PGA3-27324	1.107-127.0	2.5	2700	1650	Honda GX200	196	196 lbs
PGA4-35324	1.107-128.0	3.7	3500	1200	Honda GX390	389	249 lbs

Model #	Part #	GPM	PSI	Pump RPM	Engine	CCs	Ship Weight
PCA3-27324	1.107-124.0	2.5	2700	3400	Honda GX200	196	125 lbs
PCA3-30324	1.107-125.0	3.0	3000	3400	Honda GX270	270	148 lbs
PCA4-35324	1.107-126.0	3.8	3500	3400	Honda GX390	389	172 lbs

ACCESSORIES

Part #	Old Part #	Description
9.802-225.0		Detergent Injector Kit

- Professional-grade trigger gun and straight-through wand with handle
- Vented belt guard for cooler running belt and pulley system (PGA only)
- Two rubber feet to absorb vibration and keep unit from "walking" (spring-loaded on PGA models)
- E-Z Start Valve on 3500 PSI models
- Thermal pump protector to prevent overheating in bypass mode
- Best-in-Class design for ergonomics and maneuverability
- Foldable main handle for more compact storage
- UL1776 safety certified

PGA & PCA features:

- 50' of high pressure, wire-braid hose rated for 4,000 PSI
- Pneumatic tires

Outdoors/Indoors | Gasoline or Electric Powered | Direct-Driven Pump

PD: The Professional, Portable, Direct-Drive Cold Water Pressure Washers

The PD is LANDA's professional direct-drive, cold water pressure washer line offering models and cleaning power of up to 3,500 PSI.

Only high quality components are used on the PD, including most models carrying the tri-plunger high-pressure LANDA pump with 7-year warranty, industrial-duty Honda engines, durable welded steel frame, and side-grip wand for cleaning effectiveness. The PD is certified to the rigid UL-1776 safety standards and has a 24-inch hose guard for burst protection.



PD4-35324

Model #	Part #	GPM	PSI	Pump	Pump RPM	Engine	CCs	Ship Weight
PD3-23327	1.107-092.0	2.3	2300	Legacy	3400	Honda GC160	160	72 lbs
PD3-23326	1.107-091.0	2.3	2300	Comet	3400	Honda GC160	160	73 lbs
PD3-27324	1.107-094.0	2.5	2700	LANDA	3400	Honda GX200	196	99 lbs
PD4-35324	1.107-096.0	3.8	3500	LANDA	3400	Honda GX390	389	157 lbs

Pallet Savings	Part #	Description
8-PD3-23327	8.917-660.0	Pallet with 8 of PD3-23327
8-PD3-23326	8.917-659.0	Pallet with 8 of PD3-23326
8-PD3-27324	8.917-662.0	Pallet with 8 of PD3-27324
2-PD4-35324	8.917-664.0	Pallet with 2 of PD4-35324
(Mixed Pallet)	8.917-665.0	Pallet with 5 of PD3-23327 and 3 of PD3-27324
(Mixed Pallet)	8.917-666.0	Pallet with 5 of PD3-23326 and 3 of PD3-27324



PD features:

- Up to 3.8 GPM, 3,500 PSI
- Industrial-grade, direct-drive LANDA pump with 7-year warranty or Comet or Legacy axial pump with 1-year warranty
- Reliable Honda engines with 3-year warranty (2-year warranty on 160cc models)
- E-Z pull starting on 389cc model
- 50 ft. steel-wire braid hose (25 ft. hose on 160cc models)
- Convenient hose and gun hangers
- Easy-to-attach detergent injector and soap nozzle



PD3-23327

PD3-27324

- Fatigue-free trigger gun with side-grip spray wand
- Four quick-couple color-coded hardened stainless steel nozzles
- Welded steel chassis with pneumatic tires

ZEF: LANDA's Toughest Direct-Drive Hand-Held Cold Water Pressure Washer

LANDA's ZEF cold water pressure washer has a flexible design and industrial features that make it ideal for indoor applications. Features include:

QUALITY in the rugged frame, a LANDA pump with 7-year warranty and industrial-strength low RPM motor.

CONVENIENCE with the total package designed for cleaning in a tight, indoor facility, including a wall shelf, a remote on-off switch, auto-start-stop feature, an extra set of illustrated warning and operational stickers for posting at eye level. The ZEF is ideal for cleaning the work area and equipment.



Model #	Part #	GPM	PSI	Pump RPM	Electrical V/Ph/Amp	Motor HP	Ship Weight
ZEF2-14024D	1.107-090.0	1.8	1400	1725	120/1/20	2	110 lbs

OPTIONS AND ACCESSORIES

Part #	Old Part #	Description
8.903-613.0	35-610	Wall Shelf and Wand Holder

- 1.8 GPM, 1,400 PSI
- Auto start-stop feature
- Direct-drive LANDA Pump with 7-year warranty
- Up to 180°F inlet water
- Industrial-strength motor
- UL-1776 safety certified
- Optional wall shelf

Optional wall shelf and wand holder



PRESSURE WASHERS

Cold Water | Gasoline/Electric Powered

Outdoors/Indoors | Gasoline or Electric Powered | Direct-Driven Pump

ZG & ZE: *The Light-Duty, Hand-Held Cold Water Pressure Washers Weighing Only 65 Lbs.*

LANDA's Light Duty cold water line features the ZG and ZE, the most rugged, economy, hand-held pressure washers.

The ZG model is powered by a Honda engine with low-tone muffler and is direct coupled to an axial high-pressure pump.

The ZE has a quality motor direct coupled to an axial pump.

These models feature an easy-grip handle positioned to make carrying more evenly balanced.



ZG

ZG & ZE features:

- Rubber pad feet to absorb vibration
- 25 ft. of wire braid hose rated for up to 3,000 PSI
- Insulated straight-through high pressure wand
- Insulated, two-piece wand
- 35 ft. electric cord with GFCI on ZE model
- Downstream detergent injection
- Thermal pump protector to prevent overheating in bypass mode



ZE

Model #	Part #	GPM	PSI	Pump	Pump RPM	Engine	CCs	Ship Weight
ZG3-23236	1.107-018.0	2.3	2300	Axial	3400	Honda GC160	160	77 lbs
ZG3-24334	1.107-081.0	2.3	2400	LANDA	3400	Honda GX160	163	80 lbs

Model #	Part #	GPM	PSI	Pump	Pump RPM	Electrical V/Ph/Amp	Motor HP	Ship Weight
ZE2-11026D	1.106-023.0	2.0	1000	Axial	3450	120/1/15	1.5	95 lbs

PRESSURE WASHERS

Hot Water Generators

NG & HS: *Attaches to a Cold Water Washer to Deliver Hot Water Cleaning Effectiveness*

The stationary NG-3000 is heated by natural gas (LP-gas option available) and does not require electricity. The "LM" version has a modulating gas valve to handle flow volumes over 4 GPM.

Features include a top-quality gas valve, electronic ignition (NG-3000LM only) and rupture disk for pressure buildup protection.



NG-3000



NG-3000LM
Shown with optional support table

The HS-3000 is an electric-powered, diesel/oil-heated hot-water generator that offers the added benefit of portability.

Features include 36 ft. electrical cord with GFCI and Schedule 80 heating coil with 5-year warranty.



HS-3000

Model #	Part #	Fuel	PSI	Max BTU	Ship Wt.
NG-3000	1.103-901.0	Natural Gas	3000	420,000	450 lbs
NG-3000LM	1.103-902.0	Natural Gas	3000	750,000	900 lbs

OPTIONS AND ACCESSORIES

Part #	Old Part #	Description
9.801-042.0	35-211	Kit to Convert Fuel to LP Gas (for NG-3000)
8.904-068.0	35-212	Kit to Convert Fuel to LP Gas (for NG-3000LM)
9.802-633.0	7-1010	LP Regulator Assembly
9.801-040.0	7-10031	Draft Diverter, 10" (NG-3000)
8.717-730.0	7-10032	Draft Diverter, 12" (NG-3000LM)
8.912-689.0	95-07163653	Support Table, 8" (for NG-3000LM)

Model #	Part #	GPM	PSI	Volt/Ph/Amps	BTU	Ship Wt.
HS-3000	1.103-900.0	up to 6	3000	120/1/5	420,000	425 lbs

OPTIONS AND ACCESSORIES

Part #	Old Part #	Description
8.903-530.0	30-512	Stainless Steel Outer Wrap
8.931-276.0		Stainless Steel Top Wrap with Black Bottom Wrap
8.711-858.0	4-02750001	175' Cox Hose Reel
9.804-067.0	4-02755030	100' E-Zee Hose Reel
8.903-522.0	30-5022	E-Zee Hose Reel Mounting Kit

Outdoors | Gasoline Powered | Diesel/Oil Heated

ECOS-7000: *Environmentally Friendly Mobile Wash and Reclaim System*

LANDA's revolutionary ECOS Mobile Wash/Reclaim System recovers, cleans and recycles the dirty water from pressure washing for safe disposal or reuse—meeting most municipal and environmental regulations. And the fuel burner savings from the patent-pending Trans-Heat Technology allows for a fast return on investment.

For a better tomorrow...
clean green with LANDA!



SPECIFICATIONS

Pressure Washer System

- Volume** 4.7 GPM
- Pressure** 3,500 PSI
- Engine** Honda GX660, 688cc
- Engine Fuel** Gasoline (17 gallon tank)
- Pump** LANDA LT (1360 RPM)
- Generator** 4,000 watts/120VAC
- Wand Assembly** Variable pressure wand with 50' hose
- Detergent** Downstream detergent injector

Heating System

- Pre-Heating** Patent-pending Trans-Heat Technology
- Coil** 1/2" Schedule 80
- Burner Fuel** Diesel/kerosene/fuel oil (17 gallon tank)
- BTUs** 440,000

Vacuum System

- Suction** 105 CFM
- Hose** 50' x 2" diameter

Multi-Stage Filter System

- Pre-Filter** 50 mesh/100 micron duo-polyester bag
- Oil Removal** Oil skimmer bag
- Sediment** 20 micron pleated polyester
- Polish** 5 micron carbon

Trailer

- Water Tank Capacity** 400 gallons
- Load** 7,000 lb. capacity
- Trailer Axles** Dual, 3,500 lbs. each with electric brakes
- Wheels** 15-inch wheels, ST205/75/R15 tires
- Swing-Away Tongue** 7,500 lb. capacity with 2 5/16 inch ball coupler
- Swivel Jack** 2,000 lb. capacity
- Safety Chains** Dual 5/16 inch steel link with latching hooks
- Lighting** DOT Approved Recessed lights
- Dimensions** 174"L x 75"W x 73.5 "H (with swing-away tongue extended)
- Dry Weight** 2,865 lbs.
- Shipping Dimensions** 161"L x 85"W x 82"H (pallet & crate)
- Shipping Weight** 3,500 lbs.

Model #	Part #	GPM	PSI	Pump RPM	Engine	CCs	Ship Weight
ECOS-7000	1.103-825.0	4.7	3500	1360	Honda GX660	688	3,500 lbs

A C C E S S O R I E S

Part # Description

REPLACEMENT FILTERS

- 8.726-045.0 5 micron Carbon Filter Cartridge
- 8.726-044.0 20 micron Pleated Filter Cartridge
- 8.726-042.0 Pre-Filter Sock
- 8.726-046.0 Oil Skimmer



The ECOS-7000 trailer features an open galley with storage for the vacuum hose and non-tipping suction head under the floor. Filter cartridges are easy to access for maintenance.

Outdoors | Diesel or Gasoline Powered | Diesel/Oil Heated

TRV-3500: Customized, Trailer-Mounted Hot Water Pressure Washer System



The TRV-3500 trailer is made of extra-rugged 2-by-4 inch 10-gauge formed channel. The wheel and axle assembly feature leaf-spring suspension of up to 3,500 lbs. and 15-inch, white rimmed wheels. A powder-coated epoxy finish gives the entire package added weather protection.

Customize your TRV-3500 trailer is an easy to step process:

Step 1: Select from four series of portable, self-contained, industrial-grade hot-water pressure washers.

Step 2: Add any options and accessories, such as hose reels, rear utility rack, side saddle tool boxes, etc. to enhance the performance.

TRV-3500 features:

- Heavy-duty chassis with recessed lights
- Swing-away tongue to reduce required storage area
- 1,000 lb. swivel jack to easily maneuver unhitched trailer
- 3-way ball valve for easy switching of the water flow from the holding tank to a faucet
- 200 gallon white high-density polyethylene water tank with a 12-inch access port, 1½-inch drain valve, ¾-inch float valve and a 50-mesh inlet filter
- 15-inch, white rimmed wheels and sturdy fenders
- Optional hydraulic or electric brakes, hose reels, rear-mount utility rack, side saddle boxes and rock guard

Model #	Part #	Axle	Load Capacity	Water Tank	Ship Weight
TRV-3500	1.103-820.0	Single	3000 lbs	200 gal	1072 lbs

OPTIONS AND ACCESSORIES

Part #	Description
--------	-------------

FACTORY INSTALLED OPTIONS

- 8.917-299.0 PGHW Mounting Assembly (except PGHW5-5024E)
- 8.917-300.0 MHP Mounting Assembly
- 8.917-399.0 PGDC Mounting Assembly
- 8.917-301.0 MHC Mounting Assembly
- 8.917-398.0 Hydraulic Brakes
- 8.917-397.0 Electric Brakes
- 8.917-553.0 Break-away Kit (available only with Electric Brakes)
- 8.917-554.0 High Pressure 100 ft Hose Reel (hose not included)
- 8.917-555.0 Low Pressure 100 ft Hose Reel (hose not included)
- 8.917-556.0 Saddle Boxes (2 boxes, factory installed)
- 8.917-557.0 Rock Guard (factory installed)

FIELD KITS

- 8.917-560.0 Utility Rack (rated for up to 150 lbs, field installed)
- 8.917-558.0 Saddle Box (each, field installed)
- 8.917-559.0 Rock Guard (field installed)

Outdoors | Diesel or Gasoline Powered | Diesel/Oil Heated

TR-6000 / 3500: Top-Quality Trailer Packages Designed for Ease in Customizing

TR-6000

Accommodates these LANDA Pressure Washers: SLT (Gasoline-powered), PGHW, PGDC, MHP



Shown with optional pressure washer, fuel & tool box, hose reels and chrome fender and wheels.

Model #	Part #	Axle	Load Capacity	Water Tank	Ship Weight
TR-6000	1.103-804.0	Tandem	6000 lbs	330 gal	1080 lbs
TR-3500	1.103-801.0	Single	3300 lbs	200 gal	720 lbs

Shown with optional PGHW pressure washer, hose reels, and chrome fender and wheels.



TR-3500

Accommodates these LANDA Pressure Washers: PGHW (except 5-50524E, PGDC, MHP)

LANDA has made customizing a trailer-mounted wash system for on-site cleaning as easy as 1-2-3.

Step 1: Choose from two rugged trailers—the dual-axle TR-6000 or the single-axle TR-3500.

Step 2: Select one of LANDA's portable, industrial-grade, hot-water pressure washers to be mounted on at least one of the trailers to create a contract cleaner's dream.

Step 3: Add any or all of a broad selection of options and accessories, such as hose reels, chrome coverings, work lamp, etc. A full list is below.

Both trailers are made of extra-rugged 2-by-3 inch structural tubing. The wheel and axle assembly feature leaf-spring suspension of up to 3,500 lbs. per axle and 15-inch, white spoke wheels. A powder-coated epoxy finish gives the entire package added weather protection.

TR features:

- All electrical wiring is recessed within the tubular frame
- Lighted license plate holder and recessed tail lights
- 1,000 lb. swivel jack with a 2⁵/₁₆-inch ball coupler for quick and easy hook up of the trailer
- Two 3-way ball valves for easy switching of the water flow from the holding tank to a faucet
- Durable steel cage for holding the tank and pressure washer in place
- High-density, polyethylene water tank with a 12-inch access port, 1½-inch drain valve, ¾-inch float valve and a 50-mesh inlet filter; and two 5/16-inch chains for additional safety

O P T I O N S A N D A C C E S S O R I E S

Part #	Old Part #	Description
BRAKES		
8.902-437.0	25-1000	Kit, Electric Brakes (per axle) for TR-6000 only
8.902-438.0	25-1001	Kit, Surge Brakes (per axle) for TR-6000 only (2-inch ball hitch)
8.902-440.0	25-1003	Kit, Electric Brakes (per axle) for TR-3500 only
8.902-441.0	25-1004	Kit, Surge Brakes (per axle) for TR-3500 only (2-inch ball hitch)
8.707-506.0	25-0050	Kit, Breakaway, Electric Brakes
8.902-439.0	25-1002	Kit, Surge Brakes, Lunette Eye (per axle) for TR-6000 only
8.902-442.0	25-1005	Kit, Surge Brakes, Lunette Eye (per axle) for TR-3500 only
CHEMICAL RACK		
8.912-409.0	95-07150035	2-5 gal. Bucket Chemical Rack
WHEELS AND FENDERS		
8.902-466.0	25-1040	Upgrade to Chrome Wheels (per pair)
8.902-468.0	25-1046	Upgrade to Chrome Fender Assembly for Tandem Axle (per pair)
8.902-467.0	25-1045	Upgrade to Chrome Fender Assembly for Single Axle (per pair)
8.707-493.0	25-0021	Chrome Wheel with ST205/75D15/C Tire (each) [Spare]

Part #	Old Part #	Description
HOSE REEL KITS (Hose NOT Included)		
8.902-447.0	25-1010	Kit, LANDA Hose Reel for 75 ft. of 3/8-inch High-Pressure Hose
8.902-448.0	25-1011	Kit, LANDA Hose Reel for 175 ft. of 3/8-inch High-Pressure Hose
8.902-449.0	25-1012	Kit, LANDA Hose Reel for 75 ft. of 3/4-inch Garden Hose
LUNETTE EYE COUPLER (Replaces Standard Ball Hitch)		
8.902-436.0	25-0105	Kit, Adjustable Height Lunette Eye Coupler (2-inch)
MOUNTING KITS		
8.902-463.0		Kit, Mounting & Plumbing for SLT*
8.902-454.0	25-1020	Kit, Mounting & Plumbing for SGHW, SDHW, PGHW5-50524E*
8.917-262.0		Kit, Mounting & Plumbing for PGHW5-4-30324E
8.917-263.0		Kit, Mounting & Plumbing for PGHW5-30224E
8.917-264.0		Kit, Mounting & Plumbing for PGHW5-35324E, 4-40324E
8.902-456.0	25-1021	Kit, Mounting & Plumbing for PGDC, MHP
SIGNAGE PLATE		
8.902-469.0	25-1050	Signage Plate
VINYL SKID COVERS		
8.709-109.0	2-9025	Vinyl Skid Cover for SGHW, SDHW
8.749-946.0		Vinyl Skid Cover for PGHW, PGDC

*TR-6000 only