



## T26 - T48 - T63 Industrial Vacuums



# Solid. Reliable. Effective.

## Nilfisk CFM T Series: Three-phase Industrial Vacuums



T Series

Introducing Nilfisk CFM's new generation of three-phase industrial vacuums, the T Series. Comprised of the T26, T48 and T63, these reliable machines feature solid construction and strong performance at an affordable price. Ideal for collection of powders, liquids, dust and debris, the vacuums are easy to use and maintain - even in the most challenging environments.

- Lightweight and highly maneuverable, the T Series vacuums feature rear swiveling wheels with locking brakes.
- A unique release lever lowers the wheeled collection container and acts as a handle for fast and easy disposal of collected debris.
- An optional HEPA filter ensures that 99.995% of particles are retained, down to and including 0.18 microns in size. This exceeds HEPA filter standards.
- The T26, T48 and T63 are compatible with a wide range of Nilfisk CFM attachments and hoses to meet specific application requirements. For example, a 40 liter swarf basket and wet shut-off valve are available for metalworking applications.



| Description                  | Units          | T26                    | T48                    | T63                    |
|------------------------------|----------------|------------------------|------------------------|------------------------|
| Voltage @ 60Hz               | Volts          | 200-240/440-480        | 200-240/440-480        | 200-240/440-480        |
| Power, max                   | kW             | 2.6                    | 4.8                    | 6.3                    |
| Waterlift, max               | Inches H2O     | 82.6                   | 140.5                  | 82.6                   |
| Airflow, max                 | cfm            | 222.4                  | 222.4                  | 345.3                  |
| Filter Area, main            | Square ft.     | 21                     | 21                     | 21                     |
| Filter Area, optional HEPA   | Square ft.     | 37.7                   | 37.7                   | 37.7                   |
| Noise Level, 3' 3" (1 meter) | dB(A)          | 71                     | 74                     | 74                     |
| Protection Class             | IP             | 55                     | 55                     | 55                     |
| Insulation Class             | Class          | F                      | F                      | F                      |
| Tank Capacity                | Gallons/liters | 26 / 100               | 26 / 100               | 26 / 100               |
| Machine Inlet                | mm             | 70                     | 70                     | 70                     |
| Cord Length                  | Feet           | 30                     | 30                     | 30                     |
| Filter Efficiency, HEPA      | MPPS tested    | 99.995% @ 0.18 microns | 99.995% @ 0.18 microns | 99.995% @ 0.18 microns |
| Dimensions (L x W x H)       | inches         | 44.5 x 23.6 x 60.2     | 44.5 x 23.6 x 60.2     | 44.5 x 23.6 x 60.2     |
| Weight                       | lbs            | 251.3                  | 297.6                  | 306.4                  |

\* Specifications are subject to change without notice.

**Construction:** The T Series is constructed of heavy duty steel and polypropylene.

**Filtration systems:** The main filter is available in Standard Polyester, Polyurethane or PTFE Membrane, Nomex (high-temperature) and Antistatic. Oversized versions are also available.

**Filter cleaning systems:** The T series machines come standard with a manual filter shaker that quickly removes caked on dust from the filter's surface, maintaining the vacuum's maximum suction power and improving productivity.

**Collection options:** For safe collection and easy disposal, the T26, T48 and T63 are available with a dust bag, safe bag, or Longopac® Collection System, which allows for the collection of material in an "endless" bag that can be filled with the desired quantity, cut, sealed, disposed and immediately restored for a new use.



Liquid cut-off system (optional)



Manometer



Optional HEPA Filter



Longopac® Collection System

Distributed by:



1150 Davis Road, Suite J, Elgin, IL 60123  
 P: (847) 468-8800 • (800) 788-8867 • F: (847) 468-8811  
 www.lorchem.com • info@lorchem.com

We Know How To Get Things **CLEAN**